



Switch UBIQUITI USW-24-POE Type L2 PoE+ ports 16 95 Watts USW-24- POE



Model: USW-24-POE

Manufacturer: UBIQUITI

EAN: 817882028554

Product Code: 1186702

R10,148

Second-Generation UniFi Switching

We've redesigned our UniFi Switches from the ground up.

Near Silent Cooling

Our new airflow design reduces the need for fan usage.

Redundant Power System

UniFi SmartPower RPS, USP-RPS, is our PSU failover system.

Power Supply Failure

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

In the event of a UniFi switch power supply failure, the USP-RPS automatically supplies redundant power to the failed device.

UniFi SmartPower

One UniFi SmartPower device can support up to 6 devices until the failed device is replaced.

Touchscreen Display

The 1.3" touchscreen display allows easy monitoring and quick troubleshooting.

Summary: Ubiquiti UniFi 24-Port PoE. Switch type: Managed, Switch layer: L2/L3. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 24. Full duplex. Switching capacity: 52 Gbit/s. Networking standards: IEEE 802.3af, IEEE 802.3at. DC input voltage: 44 - 57 V. Power over Ethernet (PoE). Rack mounting, Form factor: 1U | Vendor Homepage: <https://switch.ui.com/gen2/> | Perjungimo tipas: Valdomas | Perjungimo sluoksnis: L2/L3 | Pagrindinių perjungimo RJ-45 ethernet prievadų skaičius: 24 | Pagrindinių perjungimo RJ-45 ethernet prievadų tipas: Gigabit Ethernet (10/100/1000) | SFP modulio angų kiekis: 2 | Tinklo standartai: IEEE 802.3af/IEEE 802.3at | Portų mirroring: Taip | Pilnai abipusis (duplex): Taip | Aprėpties medžio protokolas: Taip | Auto MDI/MDI-X: Taip | Srauto kontrolės palaikymas: Taip | VLAN palaikymas: Taip | Perjungimo pajėgumas: 52 | Pralaidumas: 26000 | Persiuntimo dažnis: 38.69 | Statinis maršrutas: Taip | Jumbo Frames palaikymas: Taip | Authentication type: IEEE 802.1x,RADIUS | Stovo montavimas: Taip | Forma: 1U | Produkto spalva: Sidabras | LED indikatoriai: Aktyvumas/Greitis/Jungtis/PoE/Sistema | Pridėtas maitinimo šaltinis: Taip | AC įėjimo įtampa: 100 - 240 | AC įėjimo dažnis: 50 - 60 | DC įėjimo įtampa: 44 - 57 | Maitinimas per Ethernetą (PoE): Taip | Maitinimo per Ethernetą plus (PoE+) prievadų skaičius: 16 | Maitinimo per Ethernetą (PoE) galia prievadui: 32 | Bendrosios galios per Ethernetą (PoE) charakteriskos: 92 | Darbo temperatūros diapazonas (TT): -5 - 40 | Darbo santykinės drėgmės diapazonas: 10 - 90 | Plotis: 442.4 | Ilgis: 200 | Aukštis: 43.7 | Svoris: 3000 | Sertifikavimas: CE, FCC, IC | Darniosios sistemos (DS) kodas: 85176990 | Bruto svoris: 4.57 | Neto svoris: 3 | Vienetų skaičius vienoje siuntimo dėžėje: 2 | Vieneto plotis: 31 | Vienetų skaičius ant paletės: 0 | Shipping Box Height: 34.5 | Vieneto gylis: 52 | Vieneto aukštis: 12 | Name: NET SWITCH 24PORT 1000M 2SFP/POE USW-24-POE UBIQUITI | Model name: USW-24-POE

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950