



## Switch UBIQUITI Pro Max 48 PoE Type L3 720 Watts USW-PRO- MAX-48-POE



Model: USW-PRO-MAX-48-POE

Manufacturer: UBIQUITI

EAN: 810084692721

Product Code: 1186790

## R31,356

A 48-port, Layer 3 Etherlighting™ switch with 2.5 GbE and PoE++ output.

- Etherlighting™ ports that illuminate to indicate port location, speed/link, and native VLAN/network
- (16) 2.5 GbE ports including (8) PoE+ and (8) PoE++
- (32) GbE ports including (24) PoE+ and (8) PoE++
- (4) 10G SFP+ ports
- DC power backup ready
- 720W total PoE availability
- Managed with UniFi Network 8.0.24 and later

Summary: Ubiquiti UniFi Pro Max 48 PoE. Switch type: Managed, Switch layer: L3. Basic switching RJ-

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 48. MAC address table: 32000 entries, Switching capacity: 224 Gbit/s. Networking standards: IEEE 802.1x. Power connector: AC-in jack. Power over Ethernet (PoE). Rack mounting, Form factor: 1U | Vendor Homepage: <https://eu.store.ui.com/eu/en/pro/category/switching-professional-max/collections/unifi-switching-pro-max/products/usw-pro-max-48-poe?variant=usw-pro-max-48-poe-eu> | Switch type: Managed | Switch layer: L3 | Quality of Service (QoS) support: Yes | Basic switching RJ-45 Ethernet ports quantity: 48 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Gigabit Ethernet (copper) ports quantity: 32 | 2.5G Ethernet (copper) ports quantity: 16 | SFP+ module slots quantity: 4 | Power connector: AC-in jack | Networking standards: IEEE 802.1x | 10G support: No | Port mirroring: Yes | Broadcast storm control: Yes | Flow control support: Yes | IPv4 routes: 12000 | Rate limiting: Yes | VLAN support: Yes | Virtual LAN features: Voice VLAN | Number of VLANs: 1000 | Switching capacity: 224 | Throughput: 112 | Forwarding rate: 167 | MAC address table: 32000 | Static route: Yes | Jumbo frames support: Yes | Packet buffer memory: 2 | DHCP features: DHCP guarding/DHCP relay/DHCP server/DHCPv6 snooping | IGMP snooping: Yes | Loop protection: Yes | Rack mounting: Yes | Form factor: 1U | Product colour: Grey | Housing material: SGCC | Reset button: Yes | LED indicators: System | Backlight display: Yes | Display type: LCM | Power source: AC | Power supply included: Yes | Redundant power supply (RPS) support: Yes | AC input voltage: 100 - 240 | AC input frequency: 50/60 | Power consumption (max): 820 | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) type supported: PoE+/PoE++ (4PPoE) | Power over Ethernet plus (PoE+) ports quantity: 32 | Power over Ethernet 4PPoE (PoE++) ports quantity: 16 | Power over Ethernet (PoE) voltage: 57 | Power over Ethernet (PoE) power per port: 15.4 | Total Power over Ethernet (PoE) budget: 720 | Operating temperature (T-T): -5 - 40 | Operating relative humidity (H-H): 10 - 90 | Heat dissipation: 341.2 | Width: 442.4 | Depth: 399.6 | Height: 43.7 | Weight: 6200 | Cables included: Power | Manual: Yes | Rack mount kit: Yes | Sustainability compliance: Yes | Compliance certificates: CE/Federal Communications Commission (FCC)/Industry Canada (IC)/National Defense Authorization Act (NDAA) | Unit Calculated Weight: 8.68 | Product Net Weight: 6.2 | Unit Calculated Volume: 0.04008 | Units per Shipping Box: 2 | Unit Width: 12 | Shipping Box Height: 55 | Unit Depth: 53.8 | Unit Height: 52 | Name: NET SWITCH 48PORT POE++/USW-PRO-MAX-48-POE UBIQUITI | Model: USW-PRO-MAX-48-POE | Model name: Pro Max 48 PoE

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](https://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950