



Tenda MW5S 2PACK wireless access point 1200 Mbit/s White Power over Ethernet (PoE)



Model: MW5s 2pack

Manufacturer: TENDA

EAN: 6932849428049

Product Code: 1186809

R1,993

VPN support: IPsec pass through, PPTP pass through, L2TP pass through | Certification: FCC, CE, RoHS, EAC, IC | Compatible operating systems: Android 4.0+, iOS 8+ | Power over Ethernet (PoE): Yes | Width: 91 mm | Networking standards: IEEE 802.11r | Security algorithms: WPA2-PSK | Maximum data transfer rate (2.4 GHz): 300 Mbit/s | DHCP client: Yes | WAN connection: Ethernet (RJ-45) | Ethernet LAN (RJ-45) ports: 2 | Antennas quantity: 2 | Ethernet LAN data rates: 1000 Mbit/s | Universal Plug and Play (UPnP): Yes | Depth: 91 mm | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.11ac | Maximum data transfer rate: 1200 Mbit/s | Networking standards: IEEE 802.11b | Storage relative humidity (H-H): 5 - 90% | Operating relative humidity (H-H): 10 - 90% | Reset button: Yes | Height: 93 mm | Package type: Box | Firmware upgradeable: Yes |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Ethernet LAN data rates: 10 | Operating temperature (T-T): 0 - 40 °C | 5 GHz: Yes | Antenna direction type: Omni-directional | AC input frequency: 50 - 60 Hz | Product colour: White | Cables included: LAN (RJ-45) | Placement: Floor, Table | MIMO: Yes | Storage temperature (T-T): -40 - 70 °C | MIMO type: Multi User MIMO | Ethernet LAN data rates: 100 Mbit/s | Antenna type: Internal | Output voltage: 12 V | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.11a | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Networking standards: IEEE 802.11k | Networking standards: IEEE 802.11v | DHCP server: Yes | 2.4 GHz: Yes | Service Set Identifier (SSID) features: SSID broadcast | Antenna features: Integrated antenna | Input current: 0.6 A | LED indicators: System | Antenna gain level (max): 3 dBi | LED indicators: Signal strength | Maximum data transfer rate (5 GHz): 867 Mbit/s | AC input voltage: 100 - 240 V | Output current: 1 A

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950