



PLANET MGSW-24160F network switch Managed L2+ Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) 1U Blue

Model: MGSW-24160F

Manufacturer: PLANET

EAN: 4711213688522

Product Code: 1186815

R15,395

Weight: 3 kg | Reset button: Yes | Power consumption (max): 38 W | Quick start guide: Yes | Virtual LAN features: Port-based VLAN | MAC address table: 16000 entries | Port mirroring: Yes | MAC address auto-aging supported: Yes | Operating temperature (T-T): 0 - 60 °C | Rubber feet: Yes | Multicast support: Yes | Virtual LAN features: Protocol-based VLAN | Auto-negotiation: Yes | Switching capacity: 48 Gbit/s | Console port: RS-232 | Power over Ethernet (PoE): Yes | Security algorithms: SNMP | Security algorithms: SSH | System event log: Yes | Form factor: 1U | ARP inspection: Yes |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

BPDU filtering/protection: Yes | Switch layer: L2+ | Access Control List (ACL): Yes | DHCP features: DHCP client | Width: 440 mm | Jumbo frames support: Yes | Rack mounting: Yes | Harmonized System (HS) code: 85176990 | Number of trunks: 24 | IGMP snooping: Yes | Spanning tree protocol: Yes | Jumbo frames: 10000 | Auto-edge port: Yes | DHCP features: DHCP server | Store-and-forward: Yes | Transmission distance (max): 120 km | Fiber ethernet cabling technology: 1000BASE-X | IP-MAC-Port binding: Yes | Link aggregation: Yes | Number of fans: 2 fan(s) | Stackable: Yes | Depth: 200 mm | Virtual LAN features: Private VLAN | Storage temperature (T-T): -10 - 70 °C | Security algorithms: SSL/TLS | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Storage relative humidity (H-H): 5 - 95% | LED indicators: Yes | Number of queues: 8 | Loop protection: Yes | IP routing: Yes | Switch type: Managed | Cables included: RS-232 | Height: 44.5 mm | Compatible memory cards: Not supported | Full duplex: Yes | Power over Ethernet plus (PoE+) ports quantity: 8 | Auto MDI/MDI-X: Yes | Traffic shaping: Yes | On/off switch: Yes | Operating relative humidity (H-H): 5 - 95% | Power supply included: No | Power over Ethernet (PoE) ports quantity: 8 | Admin-edge port: Yes | AC adapter included: Yes | Fiber type: Multi-mode | Terminal block included: Yes | Copper ethernet cabling technology: 1000BASE-T | MAC address auto-learning supported: Yes | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling technology: 100BASE-T | Copper ethernet cabling technology: 100BASE-FX | Traffic classification: Yes | VLAN support: Yes | Copper ethernet cabling technology: 1000BASE-TX | 10G support: No | Copper ethernet cabling technology: 100BASE-TX | Basic switching RJ-45 Ethernet ports quantity: 8 | Number of multicast groups filtered: 255 | Quality of Service (QoS) support: Yes | SSH/SSL support: Yes | Throughput: 35.6 Mpps | Rack mount kit: Yes | Terminal block port: Yes | Flow control support: Yes | SFP module slots quantity: 16 | Web-based management: Yes | MAC address filtering: Yes | AC input frequency: 50 - 60 Hz | Product colour: Blue | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1ab | Networking standards: IEEE 802.1D | Networking standards: IEEE 802.3z | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.1w | Networking standards: IEEE 802.1x | AC input voltage: 100 - 240 V | Networking standards: IEEE 802.3u

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950