



Ruijie Networks RG-NIS2100 Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black, Stainless steel

Model: RG-NIS2100-8GT2SFP-HP

Manufacturer: RUIJIE

EAN: 6976915003457

Product Code: 1187972

R7,317

Certification: IEC/EN 61000-4-2 IEC/EN 61000-4-3 IEC/EN 61000-4-4 IEC/EN 61000-4-5 IEC/EN 61000-4-6 IEC/EN 61000-4-8 | Operating temperature (T-T): -40 - 75 °C | Total Power over Ethernet (PoE) budget: 300 W | Jumbo frames: 10000 | Housing material: Metal | Jumbo frames support: Yes | Installed SFP modules quantity: 2 | Ethernet Ring Protection Switching (ERPS): Yes | Storage temperature (T-T): -40 - 85 °C | Quality of Service (QoS) support: Yes | Product colour: Stainless steel | 10G support: No | MAC address table: 8000 entries | System event log: Yes | Surge protection: Yes |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Switching capacity: 20 Gbit/s | Power over Ethernet plus (PoE+) ports quantity: 8 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Power over Ethernet (PoE): Yes | Port mirroring: Yes | Width: 50 mm | Power consumption (max): 312 W | Power source: DC/PoE | Operating relative humidity (H-H): 10 - 90% | Networking standards: IEEE 802.1Q | Operating altitude: -500 - 5000 m | Power over Ethernet 4PPoE (PoE++) ports quantity: 1 | Surge protection voltage: 6 kV | DIN rail mounting: Yes | Rack mount kit: Yes | Depth: 155 mm | Web-based management: Yes | Power supply included: Yes | Power over Ethernet (PoE) ports quantity: 8 | Height: 30 mm | Number of power supply units: 1 | Product colour: Black | Cloud-managed: Yes | Reset button: Yes | Mean time between failures (MTBF): 200000 h | Switch type: Managed | Storage relative humidity (H-H): 5 - 95% | DHCP features: DHCP snooping | Switch layer: L2 | Heat dissipation: 1067.04 BTU/h | Weight: 790 g | Package weight: 1.1 kg | Compliance certificates: CE | Warranty period: 5 year(s) | DHCP features: DHCP client | Wall mountable: Yes | Manual: Yes | Power over Ethernet (PoE) type supported: PoE+ | Number of fans: 0 fan(s) | Rack mounting: Yes | Power supply location: Internal | Forwarding rate: 14.8 Mpps | VLAN support: Yes | Compliance certificates: Federal Communications Commission (FCC) | DC voltage range: 46 - 57 V | Number of VLANs: 16 | Power over Ethernet (PoE) type supported: PoE++ (4PPoE) | Broadcast storm control: Yes | Power saving mode (EEE): Yes | Basic switching RJ-45 Ethernet ports quantity: 8

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950