CSSi SA - "Securing Tomorrow, Today"
Waterfall Office Park, 28 Augrabies Rd Vorna Valley, Midrand, 1685
Generated: 2026-10-30 15:28

TP-Link 16-Port Gigabit Desktop Switch with 16-Port PoE+

Model: TL-SG116P

Manufacturer: TP-LINK

EAN: 4895252500301

Product Code: 1187977

R3,091

Copper ethernet cabling technology: 100BASE-TX | Copper ethernet cabling technology: 10BASE-T | Package height: 70 mm | Gigabit Ethernet (copper) ports quantity: 16 | Operating temperature (T-T): 0 - 40 °C | Store-and-forward: Yes | AC input voltage: 220 V | Power over Ethernet (PoE): Yes | Link aggregation: Yes | Package width: 227 mm | LED indicators: Yes | Operating relative humidity (H-H): 10 - 90% | IGMP snooping: Yes | Width: 286 mm | Basic switching RJ-45 Ethernet ports quantity: 16 | Copper ethernet cabling technology: 1000BASE-T | Heat dissipation: 490.55 BTU/h | Switch type: Unmanaged | Power supply included: Yes | Auto MDI/MDI-X: Yes | Broadcast storm control: Yes | VLAN support: Yes | AC input frequency: 50 Hz | Input current: 0.6 A | Loop protection: Yes | Power consumption (typical): 11.72 W | Packet buffer memory: 4.1 MB | Port mirroring: Yes | Jumbo frames: 9000 | DC input voltage: 9 V | MAC address table: 8000 entries | Auto-negotiation: Yes | Jumbo frames support: Yes | Number of queues: 4 | Networking standards: IEEE 802.1Q | Quick start guide: Yes | Switching capacity: 32 Gbit/s | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Wall mountable: Yes | Height: 25.4 mm | Rate limiting: Yes | Housing material: Metal | Full duplex: Yes | Cable types supported: Cat3 | Product

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

colour: Black | Package depth: 434 mm | Number of VLANs: 32 | Cable types supported: Cat5 | Cable types supported: Cat5e | Cable types supported: Cat4 | Power consumption (max): 144.28 W | Cable types supported: Cat6 | Cable length detection: Yes | Flow control support: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Forwarding rate: 23.81 Mpps | Package weight: 2 kg | Storage relative humidity (H-H): 5 - 90% | Depth: 111.7 mm | Stackable: Yes | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Virtual LAN features: Protocol-based VLAN | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Virtual LAN features: Tagged VLAN | Networking standards: IEEE 802.3u | Warnings: Do not open the case or try to repair it yourself.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950