# PLANET IGS-10020PT network switch Managed L3 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Blue, White

Model: IGS-10020PT

Manufacturer: PLANET

EAN: 4711213689550

Product Code: 1187991

## R11,289

Certification: FCC Part 15 Class A, CE | Throughput: 14.8 Mpps | Fiber optic connector: MiniGBIC | Jumbo frames support: Yes | Gigabit Ethernet (copper) ports quantity: 8 | DIN rail mounting: Yes | Link aggregation: Yes | SFP module slots quantity: 2 | Store-and-forward: Yes | Multicast support: No | International Protection (IP) code: IP30 | Wall mountable: Yes | Power requirements: 48VDC | Management protocols: SSH, SSL, SNMP, Telnet | Depth: 107.3 mm | Product colour: White | Product colour: Blue | 10G support: No | Storage temperature (T-T): -40 - 85 °C | Quality of Service (QoS)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

support: Yes | Number of VLANs: 255 | Height: 152 mm | LED indicators: Yes | Access Control List (ACL): Yes | Switching capacity: 26 Gbit/s | Switch type: Managed | Power consumption (max): 255 W | Number of queues: 8 | Weight: 1.03 kg | Operating relative humidity (H-H): 5 - 95% | Switch layer: L3 | Full duplex: Yes | Flow control support: Yes | Power over Ethernet (PoE): Yes | Auto MDI/MDI-X: Yes | Console port: RJ-45 | Power over Ethernet (PoE) ports quantity: 8 | Port mirroring: Yes | MAC address table: 8000 entries | Networking standards: IEEE 802.1ab | Security algorithms: SSL/TLS | Operating temperature (T-T): -40 - 75 °C | Total Power over Ethernet (PoE) budget: 240 W | Web-based management: Yes | Networking standards: IEEE 802.1ad | Security algorithms: 802.1x RADIUS | Networking standards: IEEE 802.1Q | Width: 76.8 mm | Rack mounting: No | Security algorithms: SSH | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.1w | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Networking standards: IEEE 802.3u | MIB support: RFC 1213 MIB-II, IF-MIB, MAU-MIB | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.3ah | Housing material: Aluminium | Networking standards: IEEE 802.1D | Networking standards: IEEE 802.3z | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.1x | Networking standards: IEEE 802.3bz | Harmonized System (HS) code: 85176990 | Networking standards: IEEE 802.3af | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling technology: 100BASE-TX | Basic switching RJ-45 Ethernet ports quantity: 8 | Copper ethernet cabling technology: 1000BASE-T | VLAN support: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950