



PLANET IGS-10020HPT network switch Managed L2+ Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black, White

Model: IGS-10020HPT

Manufacturer: PLANET

EAN: 4711213689116

Product Code: 1187992

R12,700

Certification: FCC Part 15 Class A, CE | Web-based management: Yes | Wall mountable: Yes | Operating relative humidity (H-H): 5 - 95% | Throughput: 14.8 Mpps | Height: 72 mm | Virtual LAN features: Stacked VLAN | Virtual LAN features: Tagged VLAN | Depth: 107 mm | Supported network protocols: IPv4 / IPv6 | Virtual LAN features: Private VLAN | Loop protection: Yes | System event log: Yes | Fiber optic connector: MiniGBIC | SFP module slots quantity: 2 | Management protocols: Telnet, SNMP v1/v2c | Switch type: Managed | Product colour: Black | Product colour: White | 10G support:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

No | LED indicators: Yes | Access Control List (ACL): Yes | Reset button: Yes | Switch layer: L2+ | Virtual LAN features: Protocol-based VLAN | Number of IP interfaces: 8 | Fiber ethernet cabling technology: 1000BASE-BX | Fiber ethernet cabling technology: 100BASE-FX | Fiber ethernet cabling technology: 1000BASE-LX | International Protection (IP) code: IP30 | Firmware upgradeable: Yes | Multicast support: Yes | Fiber ethernet cabling technology: 1000BASE-SX | Power over Ethernet (PoE): Yes | Storage temperature (T-T): -40 - 85 °C | Quality of Service (QoS) support: Yes | Number of VLANs: 4094 | Power over Ethernet plus (PoE+) ports quantity: 8 | Full duplex: Yes | DIN rail mounting: Yes | Number of queues: 8 | IGMP snooping: Yes | Rack mounting: No | Width: 152 mm | ARP inspection: Yes | Operating temperature (T-T): -40 - 75 °C | Total Power over Ethernet (PoE) budget: 270 W | MAC address auto-aging supported: Yes | Weight: 1.68 kg | Spanning tree protocol: Yes | Jumbo frames: 9000 | BPDU filtering/protection: Yes | Input voltage: 48 V | Power consumption (typical): 31.9 W | Authentication: MAC-based authentication, Port-based authentication | Traffic classification: Yes | Port mirroring: Yes | Auto MDI/MDI-X: Yes | Flow control support: Yes | Jumbo frames support: Yes | Store-and-forward: Yes | Link aggregation: Yes | Switching capacity: 26 Gbit/s | Console port: RJ-45 | MAC address table: 8000 entries | Auto-negotiation: Yes | Harmonized System (HS) code: 85176990 | Networking standards: IEEE 802.1x | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.3at | Housing material: Aluminium | Networking standards: IEEE 802.1D | Networking standards: IEEE 802.3z | Networking standards: IEEE 802.1w | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.1ab | Security algorithms: SSL/TLS | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Networking standards: IEEE 802.1s | Security algorithms: SNMP | Broadcast storm control: Yes | Networking standards: IEEE 802.3af | Redundant power supply (RPS) support: Yes | Power over Ethernet (PoE) power per port: 36 W | Networking standards: IEEE 802.3u | Basic switching RJ-45 Ethernet ports quantity: 8 | Security algorithms: SSH | VLAN support: Yes | MAC address auto-learning supported: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950