



Switch UBIQUITI USW-FLEX-2.5G- 8-POE Desktop/pedestal 8x2.5GbE 8 USW-FLEX-2.5G- 8-POE

Model: USW-FLEX-2.5G-8-POE

Manufacturer: UBIQUITI

EAN: 810084695968

Product Code: 1189786

R5,524

Flexible, 8-port 2.5 GbE PoE++ switch with a 10 GbE RJ45/SFP+ combination uplink port that can be powered with PoE+++ or an AC power adapter*.

*AC power adapter sold separately.

- (8) 2.5 GbE PoE++ output ports

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

- (1) 10 GbE PoE+++ input port for power / SFP+ port combo (57W PoE availability with PoE+++ input / 37W PoE availability with PoE++ input / 12W PoE availability with PoE+ input)
- 196W PoE availability with optional AC power adapter

Summary: Ubiquiti UniFi Flex 2.5G PoE. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: 2.5G Ethernet (100/1000/2500), Basic switching RJ-45 Ethernet ports quantity: 8. Switching capacity: 60 Gbit/s. DC input voltage: 54 V. Power connector: DC-in jack. Power over Ethernet (PoE). Wall mountable, Form factor: Desktop/Wall-Mounting | Vendor Homepage: <https://eu.store.ui.com/eu/en/products/usw-flex-2-5g-8-poe> | Perjungimo tipas: Valdomas | Perjungimo sluoksnis: L2 | Pagrindinių perjungimo RJ-45 eterneto prievadų skaičius: 8 | Pagrindinių perjungimo RJ-45 eterneto prievadų tipas: 2.5G Ethernet (100/1000/2500) | 2,5 Gb eternetu (laidinių) lizdų skaičius: 8 | 10 Gb eternetu (varinių) lizdų skaičius: 1 | SFP+ modulio angų kiekis: 1 | Maitinimo jungtis: DC lizdas | 10G parama: Taip | Portų mirroring: Taip | Eterneto LAN duomenų perdavimo norma: 10,100,1000,2500 | Reitingo apribotojimas: Taip | Srauto kontrolės palaikymas: Taip | Transliacijos audros valdymas: Taip | Perjungimo pajėgumas: 60 | Pralaidumas: 30 | Persiuntimo dažnis: 44.64 | Jumbo Frames palaikymas: Taip | Apsauga nuo nesklandaus ryšio: Taip | Multicast palaikymas: Taip | Forma: Stalinis / tvirtinamas prie sienos | Produkto spalva: Balta | Korpuso medžiaga: Polikarbonatas (PC) | Atstatymo mygtukas: Taip | LED indikatoriai: Aktyvumas/Būsena/Energija/Jungtis/PoE | DIN bėgelių blokas: Taip | Montuojamas ant sienos: Taip | Maitinimo šaltinis: AC/DC/PoE | Pridėtas maitinimo šaltinis: Ne | DC įėjimo įtampa: 54 | Įvesties srovė: 3.9 | Galios suvartojimas (maks.): 17 | Maitinimas per Eternetą (PoE): Taip | Maitinimo per Eternetą plius (PoE+) prievadų skaičius: 8 | Maitinimo eternetu 4PPoE (PoE++) jungčių skaičius: 1 | Maitinimas per Eternetą (PoE): 57 | Maitinimo per Eternetą (PoE) galia prievadui: 15.4 | Bendrosios galios per Eternetą (PoE) charakteriskos: 196 | Darbo temperatūros diapazonas (TT): -20 - 45 | Darbo santykinės drėgmės diapazonas: 10 - 90 | Plotis: 212.9 | Ilgis: 99.4 | Aukštis: 33.5 | Svoris: 567 | Atitikties sertifikatai: CE/Federalinė ryšių komisija (FCC)/Industry Canada (IC) | Bruto svoris: 0.825 | Neto svoris: 0.567 | Vienetų skaičius vienoje siuntimo dėžėje: 12 | Vieneto plotis: 12 | Shipping Box Height: 29.4 | Vieneto gylis: 24.6 | Vieneto aukštis: 5.1 | Name: NET SWITCH 8PORT 2.5GBE/USW-FLEX-2.5G-8-POE UBIQUITI | Model: UBIQUITI Flex 2.5G PoE | Model name: USW-FLEX-2.5G-8-POE

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950