CSSi SA - "Securing Tomorrow, Today"
Waterfall Office Park, 28 Augrabies Rd Vorna Valley, Midrand, 1685
Generated: 2026-11-04 03:36



Switch UBIQUITI Type L3 PoE ports 24 600 Watts USW-PRO-HD-24-POE

Model: USW-PRO-HD-24-POE

Manufacturer: UBIQUITI

EAN: 810084696606

Product Code: 1214479

R23,527

Professional-grade, Layer 3 Etherlighting™ switch with (2) 10 GbE PoE++, (22) 2.5 GbE PoE++, and (4) 10G SFP+ ports./

Professional-grade, Layer 3 Etherlighting™ switch with (2) 10 GbE PoE++, (22) 2.5 GbE PoE++, and (4) 10G SFP+ ports.

- Etherlighting™ ports that illuminate to indicate port location, speed/link, and native VLAN/network*
- (22) 2.5 GbE, (2) 10 GbE PoE++ ports
- (4) 10G SFP+ ports
- DC power backup ready**
- 600W total PoE availability

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Long Description: Ubiquiti UniFi Pro HD 24 PoE. Switch type: Managed, Switch layer: L2/L3. Basic switching RJ-45 Ethernet ports type: 2.5G Ethernet (100/1000/2500), Basic switching RJ-45 Ethernet ports quantity: 22. MAC address table: 32000 entries, Switching capacity: 230 Gbit/s. Networking standards: IEEE 802.1x. Power connector: AC/DC. Power over Ethernet (PoE). Rack mounting, Form factor: 1U | Vendor Homepage: https://eu.store.ui.com/eu/en/products/usw-pro-hd-24-poe | Summary: Ubiquiti UniFi Pro HD 24 PoE. Switch type: Managed, Switch layer: L2/L3. Basic switching RJ-45 Ethernet ports type: 2.5G Ethernet (100/1000/2500), Basic switching RJ-45 Ethernet ports quantity: 22. MAC address table: 32000 entries, Switching capacity: 230 Gbit/s. Networking standards: IEEE 802.1x. Power connector: AC/DC. Power over Ethernet (PoE). Rack mounting, Form factor: 1U | Perjungimo tipas: Valdomas | Perjungimo sluoksnis: L2/L3 | Paslaugos kokybės (QoS) palaikymas: Taip | Pagrindinių perjungimo RJ-45 eterneto prievadų skaičius: 22 | Pagrindinių perjungimo RJ-45 eterneto prievadų tipas: 2.5G Ethernet (100/1000/2500) | 2,5 Gb eterneto (laidinių) lizdų skaičius: 22 | 10 Gb eterneto (varinių) lizdų skaičius: 2 | SFP+ modulio angų kiekis: 4 | Maitinimo jungtis: AC/DC | Tinklo standartai: IEEE 802.1x | 10G parama: Taip | Portų mirroring: Taip | IPv4 maršrutai: 12000 | Reitingo apribotojimas: Taip | Srauto kontrolės palaikymas: Taip | Transliacijos audros valdymas: Taip | VLAN palaikymas: Taip | Virtualaus vietinio tinklo ypatybės: Voice VLAN | VLANs skaičius: 1000 | Perjungimo pajėgumas: 230 | Pralaidumas: 115 | Persiuntimo dažnis: 171 | Adreso lentelės dydis: 32000 | Statinis maršrutas: Taip | Jumbo Frames palaikymas: Taip | Paketo buferio atmintis: 2 | DHCP funkcijos: DHCP guarding/DHCP relay/DHCP server/DHCP snooping | IGMP tinklinio judėjimo sekimas: Taip | Apsauga nuo nesklandaus ryšio: Taip | Multicast palaikymas: Taip | Stovo montavimas: Taip | Didinimas: Taip | Forma: 1U | Produkto spalva: Pilka | Korpuso medžiaga: SGCC plienas | Atstatymo mygtukas: Taip | LED indikatoriai: Būsena/Greitis/Jungtis | Ekrano tipas: LCM | Maitinimo šaltinis: AC/DC/PoE | Pridėtas maitinimo šaltinis: Taip | Nereikalingos maitinimo (RPS) paramos: Taip | AC įėjimo įtampa: 100 - 240 | AC įėjimo dažnis: 50/60 | Galios suvartojimas (maks.): 60 | Maitinimas per Eternetą (PoE): Taip | Maitinimo eternetu 4PPoE (PoE++) jungčių skaičius: 24 | Maitinimo per Eternetą (PoE) galia prievadui: 15.4 | Bendrosios galios per Eternetą (PoE) charakteriskos: 600 | Darbo temperatūros diapazonas (TT): -5 - 40 | Darbo santykinės drėgmės diapazonas: 10 - 90 | Plotis: 442.4 | Ilgis: 400 | Aukštis: 44 | Svoris: 6200 | Pridėti kabeliai: Energija | Stovo montavimo rinkinys: Taip | Atitikties sertifikatai: CE/Federalinė ryšių komisija (FCC)/Industry Canada (IC) | Bruto svoris: 8.38 | Neto svoris: 6.3 | Vienetų skaičius vienoje siuntimo dėžėje: 2 | Vieneto plotis: 12 | Vienetų skaičius ant paletės: 0 | Shipping Box Height: 55 | Vieneto gylis: 54 | Vieneto aukštis: 52 | Bullet Points:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

- Etherlighting™ ports that illuminate to indicate port location, speed/link, and native VLAN/network*
- (22) 2.5 GbE, (2) 10 GbE PoE++ ports
- (4) 10G SFP+ ports
- DC power backup ready**
- 600W total PoE availability

| Name: NET SWITCH 24PORT 2.5GBE POE/POE USW-PRO-HD-24-POE UBIQUITI | Model: USW-PRO-HD-24-POE

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950