



Graphics Card

ASUS AMD

Radeon RX 9060

XT 16 GB GDDR6

128 bit PCI

Express 5.0

Active DUAL-

RX9060XT-16G

Model: DUAL-RX9060XT-16G

Manufacturer: ASUS

EAN: 4711636196765

Product Code: 14587

R9,734

Dual Radeon™ RX 9060 XT

Dual Fans, Perfect Fit

ASUS Dual Radeon™ RX 9060 XT combines powerful thermal performance with broad compatibility. Advanced cooling solutions from flagship graphics cards — including two Axial-tech fans for optimizing airflow to the heatsink. Designed in a compact 2.5-slot form factor, delivering more power in less space. These enhancements make ASUS Dual the perfect choice for gamers who want heavyweight graphics performance in a compact build.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Cooling

2.5-slot Design

A carefully designed shroud, heatsink, and heatpipe layout enables the two Axial-tech fans to leverage chassis side-panel ventilation, delivering thermal performance that beyond the compact size.

Axial-tech Upgrades

Two tried-and-true Axial-tech fans feature a smaller hub facilitates longer blades and a barrier ring to increase downward air pressure.

0dB Technology

To eliminate unnecessary noise, the stop mode automatically halts all fans when the GPU temperature drops below 55°C and power consumption is low.

Dual Ball Fan Bearings

Fan bearings come in different types, each with its own advantages. Dual ball bearings provide superior durability and can last up to twice as long as sleeve-bearing designs.

Vented Backplate

A vented backplate significantly enhances heat dissipation, helping to keep the GPU cooler during intense tasks. This additional airflow helps ensure optimal temperatures, boosting performance, longevity and stability by defending against overheating and thermal throttling.

Unmatched Reliability

ASUS GPU Guard

ASUS GPU Guard applies adhesive to secure all four corners to reduce the risk of cracks.

Protective Backplate

The PCB is reinforced by a backplate that adds structural rigidity, helping to prevent flex and to protect components and trace pathways from damage.

Stainless Steel Bracket

The mounting bracket of the Dual has been beefed up with 304 Stainless Steel that's harder and

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

more resistant to corrosion.

Engineering

Dual BIOS

Do you prioritize lower core temperatures or quieter operation? Performance mode increases fan speed to keep the card running cool all the time. Quiet mode maintains the same power target and performance settings, but applies a less aggressive fan curve for quieter operation at medium temperatures. Want more control? Customize your experience with GPU Tweak III software for fine-tuned fan profiles and performance adjustments.

Auto–Extreme Technology

Auto-Extreme Technology is an automated manufacturing process that sets new standards in the industry by allowing completing all soldering to be completed in a single pass. This reduces thermal strain on components and avoids the use of harsh cleaning chemicals, resulting and minimizes in less environmental impact. The result is lower power consumption during manufacturing and a more reliable, high-quality product.lower manufacturing power consumption, and a more reliable product overall.

Summary: ASUS Dual -RX9060XT-16G. Graphics processor family: AMD, Graphics processor: Radeon RX 9060 XT. Discrete graphics card memory: 16 GB, Graphics card memory type: GDDR6, Memory bus: 128 bit. Maximum resolution: 7680 x 4320 pixels. DirectX version: 12 Ultimate, OpenGL version: 4.6. Interface type: PCI Express 5.0. Cooling type: Active, Number of fans: 2 fan(s) | Vendor Homepage: <https://www.asus.com/motherboards-components/graphics-cards/dual/dual-rx9060xt-16g/> | CUDA: No | Graphics processor: Radeon RX 9060 XT | Graphics processor family: AMD | Maximum displays per videocard: 3 | Maximum resolution: 7680 x 4320 | Parallel processing technology support: Not supported | Processor boost clock speed: 3230 | Processor boost clock speed (Gaming mode): 2640 | Processor boost clock speed (OC mode): 3250 | Stream processors: 2048 | Data transfer rate: 20 | Discrete graphics card memory: 16 | Graphics card memory type: GDDR6 | Memory bus: 128 | DisplayPort version: 2.1a | DisplayPorts quantity: 2 | HDMI ports quantity: 1 | HDMI version: 2.1b | Interface type: PCI Express 5.0 | DirectX version: 12 Ultimate | Dual Link DVI: No | HDCP: Yes | HDCP version: 2.3 | OpenGL version: 4.6 | TV tuner integrated: No | Cooling technology: ASUS Axial-tech | Cooling type: Active | Number of fans: 2 | Number of slots: 2.5 | Product colour: Black | SFF ready: Yes | Minimum system power supply: 550 | Supplementary power connectors: 1x 8-pin | Windows operating systems supported: Windows 10 x64/Windows 11 x64 |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Depth: 49 | Height: 120 | Length: 202 | Package type: Box | Manual: Yes | Model: DUAL-RX9060XT-16G | Units per Pallet: 0 | Units per Shipping Box: 8 | Unit Calculated Volume: 0.006868 | Product Net Weight: 0.55 | Unit Calculated Weight: 1.2

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950