



## Graphics Card **SAPPHIRE AMD Radeon RX 9060 XT 8 GB GDDR6 128 bit PCI Express x16 5.0 Active 11350- 05-20G**



Model: 11350-05-20G

Manufacturer: SAPPHIRE

EAN: 4895106297333

Product Code: 14617

# R8,387

### Fuse Protection

In order to protect your card, the SAPPHIRE cards have fuse protection built into the circuit of the external PCI-E power connector to keep the components safe.

### Honeywell PTM7950 TIM

The Honeywell PTM7950 Thermal Interface Material (TIM) offers a premium solution for high-

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

performance electronics, particularly in the demanding field of graphics processing units (GPUs). The PTM7950 delivers superior thermal conductivity, enhancing the reliability and longevity of graphics cards by its outstanding material characteristics.

## **AeroCurve Fan Blade**

The latest fan blade design builds upon its predecessor with advancements that reduce air friction, increasing the usable fan RPM range while maintaining low noise levels. This refined design ensures improved airflow, optimized static pressure, and enhanced cooling efficiency for demanding applications.

## **FrameDefense**

The mechanical design of the graphics card features a robust, box-like frame that ensures exceptional build quality and durability. This solid construction provides a protective enclosure for all internal components, reducing the risk of damage during handling or installation. This rigid frame offers added stability and strength, making it highly resistant to accidental impacts or pressure, ensuring that the delicate components, such as the GPU, memory, and VRMs, remain secure. With this design, users can confidently handle the card without worrying about compromising its integrity or performance.

## **Digital Power Design**

SAPPHIRE PULSE AMD Radeon™ RX 9060 Series are designed with digital power which provides accurate power control and excellent power efficiency

- GPU: Boost Clock: Up to 3130 MHz
- GPU: Game Clock: Up to 2530 MHz
- Memory: 8GB/128 bit DDR6. 20Gbps Effective
- Stream Processors: 2048
- AMD RDNA™ 4 Architecture
- Ray Accelerator: 32

Summary: Sapphire PULSE Radeon RX 9060 XT. Graphics processor family: AMD, Graphics processor: Radeon RX 9060 XT. Discrete graphics card memory: 8 GB, Graphics card memory type: GDDR6, Memory bus: 128 bit. Maximum resolution: 7680 x 4320 pixels. DirectX version: 12 Ultimate. Interface type: PCI Express x16 5.0. Cooling type: Active, Number of fans: 2 fan(s) | Vendor

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Homepage: <https://www.sapphiretech.com/en/consumer/pulse-radeon-rx-9060-xt-8g-m-gddr6> | AI accelerators: 64 | Compute units: 32 | CUDA: No | Graphics processor: Radeon RX 9060 XT | Graphics processor family: AMD | Infinity cache: 32 | Maximum displays per videocard: 3 | Maximum resolution: 7680 x 4320 | Parallel processing technology support: Not supported | Processor boost clock speed: 3130 | Processor boost clock speed (Gaming mode): 2530 | Ray accelerators: 32 | Stream processors: 2048 | Data transfer rate: 20 | Discrete graphics card memory: 8 | Graphics card memory type: GDDR6 | Memory bus: 128 | DisplayPort version: 2.1a | DisplayPorts quantity: 1 | HDMI ports quantity: 2 | HDMI version: 2.1b | Interface type: PCI Express x16 5.0 | AMD FreeSync: Yes | DirectX version: 12 Ultimate | Dual Link DVI: No | TV tuner integrated: No | Cooling technology: Sapphire Dual-X | Cooling type: Active | Number of fans: 2 | Number of slots: 2 | Product colour: Grey/White | Minimum system power supply: 450 | Supplementary power connectors: 1x 8-pin | Thermal Design Power (TDP): 150 | Linux operating systems supported: Yes | Minimum RAM: 8192 | Windows operating systems supported: Windows 10/Windows 11 | Depth: 40.6 | Height: 122 | Length: 200 | Package type: Box | Units per Pallet: 0 | Units per Shipping Box: 10 | Unit Calculated Volume: 0.00363 | Product Net Weight: 0.7 | Unit Calculated Weight: 0.873

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.