Switch MIKROTIK CRS520-4XS-16XQ-RM Desktop/pedestal 16xQSFP28 4xSFP28 1xConsole CRS520-4XS-16XQ-RM

Model: CRS520-4XS-16XQ-RM

Manufacturer: MIKROTIK

EAN: 4752224009265

Product Code: 193420

R39,827

Welcome to the forefront of networking: the future-proof CRS520-4XS-16XQ-RM with extra processing power, 4 GB of DDR4 RAM, and the best price per 100 Gigabit port we've seen so far.

With 16x 100 Gigabit QSFP28 ports, 4x 25 Gigabit SFP28 ports, and an extra pair of 10 Gigabit

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Ethernet ports, this switch can bring a lot of value to complicated enterprise networks, data centers, multimedia studios, and other setups where you would typically use several devices. Now – a single CRS520 can do the trick!

Avid CCR users might recognize the powerful quad-core ARM CPU running at 2 GHz, and ask – why would a switch need all that power? Two reasons:

1) CRS520 is more than a switch. You can run OSPF/BGP, out-of-band/management VPNs, ACLs, Jumbo frames and even L3HW Offloaded routing;

2) Future-proofing: as our friends at Marvell keep expanding the capabilities of their spectacular switch-chips, our in-house software team is busy exploring ways to add even more Hardware Offloaded features. You can expect software updates that will take the CRS520 to the next level! And all that without any paywalls or subscriptions.

Two hot-swap power supplies and four hot-swap fans for cooling are included. This switch can also be powered by the PW48V-12V150W Hot Swap -48V DC telecom power supply, available separately. Summary: Mikrotik CRS520-4XS-16XQ-RM. Console port: RJ-45. Rack mounting | Vendor Homepage: https://mikrotik.com/product/crs520_4xs_16xq_rm#fndtn-specifications | 10 Gb eterneto (varinių) lizdų skaičius: 2 | Konsolės prievadas: RJ-45 | QSFP28 prievadų kiekis: 16 | SFP28 prievadų kiekis: 4 | 10G parama: Taip | Stovo montavimas: Taip | Numatyta operacinė sistema: RouterOS | Integruotas procesorius: Taip | Procesoriaus dažnis: 2000 | Atminties tipas: Sparčioji atmintinė | Vidinė atmintis: 4000 | Flash atmintis: 128 | Vidutinis laikas tarp trikčių (MTBF): 200000 | Maitinimo šaltinis: AC | Pridėtas maitinimo šaltinis: Taip | AC įėjimo įtampa: 100 - 240 | AC įėjimo dažnis: 50/60 | Galios suvartojimas (maks.): 150 | Maitinimas per Eternetą (PoE): Ne | Darbo temperatūros diapazonas (TT): -20 - 50 | Plotis: 443 | Ilgis: 367 | Aukštis: 44 | Atitikties sertifikatai: CE/EAC/RoHS | Bruto svoris: 6.85 | Neto svoris: 6 | Vienetų skaičius vienoje siuntimo dėžėje: 1 | Vieneto plotis: 45 | Shipping Box Height: 10.5 | Vieneto gylis: 63 | Vieneto aukštis: 10.5 | Name: NET ROUTER/SWITCH 16PORT SFP28/CRS520-4XS-16XQ-RM MIKROTIK | Model name: CRS520-4XS-16XQ-RM

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950