Switch AXIS 4x10Base-T 100Base-TX 1000Base-T 1xSFP 01449-001

Model: 01449-001

Manufacturer: AXIS

EAN: 7331021063488

Product Code: 193422

R37,479

AXIS T8504-E Outdoor PoE Switch is an easy-to-install, compact outdoor switch enabling connection of four PoE-powered devices. The SFP port enables fiber connectivity for long distance connections, and remote management ensures easy maintenance, reducing support cost and customer down time. AXIS T8504-E is a robust system component with a wide temperature range, surge protection, and a dust and water-resistant enclosure which remains assembled during installation. With up to 60 W per port and a total power budget of 150 W, the switch is compatible with all Axis network devices.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

- 60 W per port, total 150 W; Plug-and-play installation; Rugged enclosure; SFP port; VAPIX® support

Summary: Axis 01449-001. Switch type: Managed. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 4. MAC address table: 8000 entries, Switching capacity: 20 Gbit/s. Networking standards: IEEE 802.1Q, IEEE 802.3af, IEEE 802.3at. Power connector: DC-in jack. Power over Ethernet (PoE) | Vendor Homepage: https://www.axis.com/gb/en/products/axis-t8504e-outdoor-poe-switch | Switch type: Managed | Basic switching RJ-45 Ethernet ports quantity: 4 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Power connector: DC-in jack | SFP module slots quantity: 1 | 10G support: No | Copper ethernet cabling technology: 1000BASE-T/100BASE-TX/10BASE-T | Networking standards: IEEE 802.1Q/IEEE 802.3af/IEEE 802.3at | VLAN support: Yes | Jumbo frames: 9216 | Jumbo frames support: Yes | MAC address table: 8000 | Switching capacity: 20 | Throughput: 14.9 | Password protection: Yes | Security algorithms: HTTPS/SNMP/SNMPv3/SSH | Supported network protocols: IPv4, IPv6, HTTP, HTTPS, Bonjour, SNMP v1/v2c/v3, DNS, TCP, UDP, IGMP, ICMP, ARP, SSH, RADIUS, TACACS, TELNET, Syslog, 802.1Q (VLAN) | Electromagnetic compatibility: EN 55032 B, EN 55024, FCC 15 B B, RCM AS/NZS CISPR 32 B, EN 61000-4-5 5, EN 50121-4, IEC 62236-4 | Housing material: Aluminium | International Protection (IP) code: IP67 | Product colour: White | Safety: IEC/EN/UL 60950-1, IEC/EN/UL 60950-22, EAC | Plug and Play: Yes | AC input frequency: 50 - 60 | AC input voltage: 100 - 240 | Surge protection: Yes | Surge protection voltage: 6 | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) power per port: 60 | Total Power over Ethernet (PoE) budget: 150 | Operating relative humidity (H-H): 0 - 90 | Operating temperature (T-T): -40 - 50 | Storage relative humidity (H-H): 0 - 90 | Storage temperature (T-T): -40 - 85 | Depth: 166 | Height: 72 | Weight: 2900 | Width: 240 | User guide: Yes | Certification: IEC 60529 IP67, NEMA 250 4X, GR-1089-CORE 4 ITU-T K.20 | Harmonized System (HS) code: 85176990 | Product Net Weight: 2.9 | Shipping Box Height: 10.1 | Unit Calculated Volume: 0.00909 | Unit Calculated Weight: 3.01 | Units per Shipping Box: 1

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950