



Switch AXIS 2x10GbE 6x1GbE 480 Watts 02621- 001



Model: 02621-001

Manufacturer: AXIS

EAN: 7331021080225

Product Code: 193429

R32,189

This rugged 8-port switch is ideal for demanding installations. Designed to withstand shock and vibrations, it can handle temperatures ranging from -40 °C to 60 °C (-40 °F to 140 °F). Each port can deliver up to 90 W PoE++ (IEEE 802.3bt) with a total power budget of 480 W. Plus, it also supports fiber ensuring flexible long-distance installations. Furthermore, featuring a familiar Axis interface with a graphic topology for easy overview of devices, AXIS D8208-R ensures easy configuration with Axis products.

- 480 W power budget; Compliant with IEEE 802.3bt up to 90 W; Familiar and intuitive Axis interface; High availability with Rapid Ring; NEMA TS-2 Compliant

Summary: Axis 02621-001. Switch type: Managed. Basic switching RJ-45 Ethernet ports type: 10G Ethernet (100/1000/10000), Basic switching RJ-45 Ethernet ports quantity: 8, Installed SFP+ modules

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

quantity: 2, Console port: RJ-45. MAC address table: 16000 entries, Switching capacity: 62 Gbit/s. Networking standards: IEEE 802.1Q, IEEE 802.1x, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt. Power over Ethernet (PoE) | Vendor Homepage: <https://www.axis.com/products/axis-d8208-r-industrial-poe-switch> | Switch type: Managed | ARP inspection: Yes | Basic switching RJ-45 Ethernet ports quantity: 8 | Basic switching RJ-45 Ethernet ports type: 10G Ethernet (100/1000/10000) | Gigabit Ethernet (copper) ports quantity: 6 | 2.5G Ethernet (copper) ports quantity: 2 | Installed SFP+ modules quantity: 2 | Console port: RJ-45 | Networking standards: IEEE 802.1Q/IEEE 802.1x/IEEE 802.3af/IEEE 802.3at/IEEE 802.3bt | 10G support: Yes | VLAN support: Yes | Virtual LAN features: Private VLAN | Switching capacity: 62 | Throughput: 46.12 | MAC address table: 16000 | Jumbo frames support: Yes | Jumbo frames: 10240 | DHCP features: DHCP snooping | Access Control List (ACL): Yes | Password protection: Yes | Security algorithms: HTTPS | Supported network protocols: IPv4, IPv6, HTTP, HTTPS, SMTP, Bonjour, UPnP®, SNMP v1/v2c/v3, DNS, NTP, RTSP, TCP, UDP, IGMP, ICMP, DHCP, ARP, SSH, RADIUS, TACACS+, Syslog, IEEE 802.1X, 802.1Q (VLAN), LLDP, LLDP-Med, STP, MSTP, RSTP, LACP, RRPP | Product colour: Black | Housing material: Aluminium | Power source: DC/PoE | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) ports quantity: 8 | Power over Ethernet (PoE) power per port: 90 | Total Power over Ethernet (PoE) budget: 480 | Operating temperature (T-T): -40 - 60 | Storage temperature (T-T): -40 - 85 | Operating relative humidity (H-H): 5 - 95 | Storage relative humidity (H-H): 5 - 95 | Width: 62 | Depth: 130 | Height: 168 | Weight: 892 | Certification: EMC EN 55035, EN 55032 Class A, EN 50121-4, EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, IEC 62236-4, FCC part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), IEC 62236-4, VCCI Class A, RCM AS/NZS CISPR 32 Class A Safety IEC/EN/UL 62368-1 ed. 3 Environment IEC 600 | Unit Calculated Weight: 1.53 | Product Net Weight: 0.6 | Unit Calculated Volume: 0.004016 | Units per Shipping Box: 1 | Unit Width: 17.5 | Shipping Box Height: 8.5 | Unit Depth: 27 | Unit Height: 8.5 | Name: NET SWITCH 8PORT POE++ D8208-R/02621-001 AXIS | Model: D8208-R

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950