



NET SWITCH 16PORT POE+ T8516/5801-692 AXIS



Model: 5801-692

Manufacturer: AXIS

EAN: 7331021055872

Product Code: 193476

R22,138

AXIS T8516 PoE+ Network Switch is an easy to install 16-port managed Gigabit switch - a perfect complement to Axis' recorders to further simplify setup and installation of surveillance systems. AXIS T8516 comes with an integrated DHCP server for automatic assignment of IP addresses and discovery of connected Axis devices. The intuitive administrator interface offers a graphic topology for easy overview of all devices in the system with information about connected devices and status. The high PoE power output allows for connection of up to 16 PoE cameras.

- 2 SFP/RJ45 Combination Ports; 30 W PoE per port, total 240 W; Gigabit switch; Intuitive graphic topology for system overview

Summary: Axis 5801-692. Switch type: Managed. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 16. MAC address table: 8000 entries, Switching capacity: 36 Gbit/s. Networking standards: IEEE 802.3af, IEEE 802.3at. Power over Ethernet (PoE) | Vendor Homepage: <https://www.axis.com/gb/en/products/power-and->

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

connectivity/axis-t8516-poe-network-switch/ | Switch type: Managed | Basic switching RJ-45 Ethernet ports quantity: 16 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Combo SFP ports quantity: 2 | Networking standards: IEEE 802.3af/IEEE 802.3at | Copper ethernet cabling technology: 1000BASE-T/100BASE-TX/10BASE-T | VLAN support: Yes | Switching capacity: 36 | Throughput: 26.8 | MAC address table: 8000 | Jumbo frames support: Yes | Jumbo frames: 9216 | Access Control List (ACL): Yes | Security algorithms: HTTPS/SNMP/SSH | Product colour: Black | Reset button: Yes | LED indicators: Activity/Link/PoE/Speed/System | AC input voltage: 100 - 240 | AC input frequency: 50 - 60 | Output power: 240 | Power consumption (max): 285 | Power over Ethernet (PoE): Yes | Operating temperature (T-T): 0 - 50 | Storage temperature (T-T): -10 - 70 | Operating relative humidity (H-H): 10 - 90 | Storage relative humidity (H-H): 5 - 95 | Width: 442 | Depth: 211 | Height: 44 | Weight: 3000 | AC adapter included: Yes | Rubber feet: Yes | Harmonized System (HS) code: 85176990 | Unit Calculated Weight: 3.87 | Product Net Weight: 3 | Unit Calculated Volume: 0.01404 | Units per Shipping Box: 1 | Unit Width: 9 | Shipping Box Height: 30 | Unit Depth: 52 | Unit Height: 30 | Name: NET SWITCH 16PORT POE+ T8516/5801-692 AXIS

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950