



ASUS DSL-AC51 wireless router Gigabit Ethernet Dual-band (2.4 GHz 5 GHz) Black

Model: DSL-AC51

Manufacturer: ASUS

EAN: 4712900688108

Product Code: 200056

R1,228

VPN support: IPSec Pass-Through PPTP Pass-Through L2TP Pass-Through PPTP server OpenVPN
server PPTP client L2TP client OpenVPN client | Certification: CE | DHCP client: Yes | DC-in jack: Yes |
Filtering: Yes | Reset button: Yes | Product colour: Black | Network address translation (NAT): Yes | AC
input frequency: 50 - 60 Hz | Width: 207 mm | Guest access: Yes | Package type: Box | DMZ support:
Yes | Ethernet LAN interface type: Gigabit Ethernet | Firewall security: Parental control | Port
forwarding: Yes | Quick start guide: Yes | Firmware upgradeable: Yes | Ethernet LAN data rates: 10 |
Weight: 440 g | 3G: No | Windows operating systems supported: Windows 7 Ultimate x64 | Windows
operating systems supported: Windows 7 x64 | Windows operating systems supported: Windows 10
Enterprise | Windows operating systems supported: Windows 7 Home Basic x64 | Windows operating
systems supported: Windows 8 Pro x64 | Windows operating systems supported: Windows 8.1 Pro |
Windows operating systems supported: Windows 10 Pro | Windows operating systems supported:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices
may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or
typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Windows 7 Home Premium | Windows operating systems supported: Windows 7 Starter | Product type: Tabletop router | Windows operating systems supported: Windows 10 Home x64 | Windows operating systems supported: Windows 8 | Cables included: DSL | AC input voltage: 100 - 240 V | Windows operating systems supported: Windows 8.1 Enterprise | Windows operating systems supported: Windows 7 Professional | Windows operating systems supported: Windows 7 | VPN Passthrough: Yes | Ethernet LAN data rates: 100 Mbit/s | AC adapter included: Yes | LED indicators: ADSL, DSL, LAN, Power, WLAN | Ethernet LAN data rates: 1000 | Windows operating systems supported: Windows 10 Home | Windows operating systems supported: Windows 7 Starter x64 | Height: 200 mm | Windows operating systems supported: Windows 10 Education x64 | Cables included: LAN (RJ-45) | Windows operating systems supported: Windows 7 Home Basic | Windows operating systems supported: Windows 7 Ultimate | Cables included: Phone (RJ-11) | Windows operating systems supported: Windows 8.1 Enterprise x64 | Windows operating systems supported: Windows 7 Home Premium x64 | Windows operating systems supported: Windows 7 Enterprise x64 | Windows operating systems supported: Windows 8.1 Pro x64 | Windows operating systems supported: Windows 8.1 x64 | Wi-Fi configuration card: Y | Windows operating systems supported: Windows 10 Pro x64 | Windows operating systems supported: Windows 8 Enterprise | Supported network protocols: IPv4, IPv6 | Wi-Fi standards: 802.11b | VDSL: Yes | Windows operating systems supported: Windows 7 Professional x64 | Windows operating systems supported: Windows 8 x64 | Windows operating systems supported: Windows 10 Education | VDSL2: Yes | Operating relative humidity (H-H): 50 - 90% | Windows operating systems supported: Windows 10 Enterprise x64 | ADSL2+: Yes | DHCP server: Yes | Ethernet WAN: Yes | USB port: No | Mac operating systems supported: Mac OS X 10.5 Leopard | Web-based setup wizard: Yes | Operating temperature (T-T): 0 - 40 °C | On/off switch: Yes | Indication light: Yes | URL filtering: Yes | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Mac operating systems supported: Mac OS X 10.7 Lion | ADSL2: Yes | Plug and Play: Yes | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | Ethernet LAN: Yes | SIM card slot: No | Power source type: AC, DC | RJ-11 ports quantity: 1 | System event log: Yes | ADSL: Yes | Port-based Network Access Control (PNAC): Yes | Output current: 1 A | Universal Plug and Play (UPnP): Yes | Depth: 175 mm | IP address filtering: Yes | Storage temperature (T-T): 0 - 70 °C | Linux operating systems supported: Yes | Management protocols: IGMP v1/v2/v3 | Ethernet LAN (RJ-45) ports: 2 | Firewall: Yes | Antenna design: External | Wi-Fi standards: 802.11g | Wi-Fi standards: 802.11a | Memory card slot(s): No | Antennas quantity: 3 | Cabling technology: 10/100/1000Base-T(X) | Windows operating systems supported: Windows 10 | Windows operating systems supported: Windows 10 IOT Core | Windows operating systems supported: Windows 8 Enterprise x64 | Windows operating systems supported: Windows 8 Pro | Windows operating systems supported: Windows 7 Enterprise | 3G/4G USB modem

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

compatibility: No | WLAN data transfer rate (second band): 433 Mbit/s | Wi-Fi standards: Wi-Fi 4 (802.11n) | Mac operating systems supported: Mac OS X 10.8 Mountain Lion | Mac operating systems supported: Mac OS X 10.1 Puma | Web-based management: Yes | Storage relative humidity (H-H): 20 - 90% | Security algorithms: 64-bit WEP | Security algorithms: WPA2-Enterprise | Security algorithms: WPA-Enterprise | Housing material: Acrylonitrile butadiene styrene (ABS) | Output voltage: 12 V | Security algorithms: WPA2-PSK | Mac compatibility: Yes | Security algorithms: 128-bit WEP | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.11a | Networking standards: IEEE 802.11e | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | DSL WAN: Yes | Mac operating systems supported: Mac OS X 10.3 Panther | Mac operating systems supported: Mac OS X 10.6 Snow Leopard | Mac operating systems supported: Mac OS X 10.4 Tiger | Mac operating systems supported: Mac OS X 10.2 Jaguar | Security algorithms: WPA-PSK | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.11ac | WLAN data transfer rate (max): 433 Mbit/s | 4G: No | WPS push button: Yes | WLAN data transfer rate (first band): 300 Mbit/s | Top Wi-Fi standard: Wi-Fi 5 (802.11ac) | Quality of Service (QoS) support: Yes | Networking standards: IEEE 802.11i | Networking standards: IEEE 802.11b | Security algorithms: WPS

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950