



Cudy GS105D network switch Unmanaged Gigabit Ethernet (10/100/1000) Black



Model: GS105D

Manufacturer: CUDY

EAN: 6971690790097

Product Code: 200084

R262

Networking standards: IEEE 802.3x | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.3i | Storage relative humidity (H-H): 5 - 90% | Basic switching RJ-45 Ethernet ports quantity: 5 | Cables included: DC | Power connector: DC-in jack | Manual: Yes | Depth: 52.5 mm | Plug and Play: Yes | Copper ethernet cabling technology: 1000BASE-T | Height: 24 mm | Copper ethernet cabling technology: 100BASE-TX | Package width: 92 mm | Switch type: Unmanaged | LED indicators: Power | Package height: 57 mm | AC input frequency: 50/60 Hz | Copper ethernet cabling technology: 10BASE-T | Power over Ethernet (PoE): No | Weight: 52 g | Switching capacity: 10 Gbit/s | LED indicators: Activity | Input current: 0.55 A | Power source: DC | Operating relative humidity (H-H): 10 - 90% | Ethernet LAN data rates: 10,100,1000 Mbit/s | Width: 88 mm | Jumbo frames support: Yes | Storage temperature (T-T): -40 - 70 °C | Product

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

colour: Black | Package weight: 137 g | Full duplex: Yes | Power supply included: Yes | AC input voltage: 100 - 240 V | LED indicators: Link | Operating temperature (T-T): 0 - 40 °C | Package type: Box | Rack mounting: No | Auto MDI/MDI-X: Yes | MAC address table: 2048 entries | Package depth: 88 mm | Packet buffer memory: 0.375 MB | Half duplex: Yes | DC input voltage: 5 V | Auto-negotiation: Yes | Forwarding rate: 7.44 Mpps | Bandwidth: 1 Gbit/s | Store-and-forward: Yes | Cable types supported: Cat3 | Jumbo frames: 15000 | Cable types supported: Cat5 | Cable types supported: Cat5e | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Warnings: Do not open the case or try to repair it yourself. | Warnings: Ensure the unit is adequately ventilated during operation.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950