



Cudy GS108 network switch Unmanaged Gigabit Ethernet (10/100/1000) Black



Model: GS108

Manufacturer: CUDY

EAN: 6971690790554

Product Code: 200085

R474

Products per master (outer) case: 40 pc(s) | Weight: 300 g | Quick start guide: Yes | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.3x | Storage relative humidity (H-H): 5 - 95% | Operating temperature (T-T): 0 - 40 °C | Power over Ethernet (PoE): No | Package width: 175 mm | Width: 138 mm | LED indicators: Link | LED indicators: Power | Power source: DC | Operating altitude: 0 - 3048 m | Product colour: Black | LED indicators: Loop | Input current: 0.55 A | Networking standards: IEEE 802.3u | Package type: Box | Cables included: DC | Package weight: 500 g | Package height: 63 mm | Storage temperature (T-T): -40 - 70 °C | Rack mounting: No | Depth: 78 mm | Package depth: 120 mm | Height: 25 mm | Operating relative humidity (H-H): 0 - 100% | Ethernet LAN data rates: 10,100,1000 Mbit/s | Switching capacity: 16 Gbit/s | Cable types supported: Cat3 | Power connector: DC-in jack | Forwarding rate: 11.904 Mpps | Copper ethernet cabling technology: 1000BASE-T | VLAN support: Yes | Basic switching RJ-45

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Ethernet ports quantity: 8 | DC input voltage: 5 V | Master (outer) case width: 505 mm | Copper ethernet cabling technology: 100BASE-TX | Full duplex: Yes | Copper ethernet cabling technology: 10BASE-T | Cable types supported: Cat5 | Cable types supported: Cat5e | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Packet buffer memory: 0.18 MB | MAC address table: 4096 entries | Master (outer) case length: 320 mm | Master (outer) case gross weight: 21 kg | Jumbo frames support: Yes | Jumbo frames: 15000 | Store-and-forward: Yes | Flow control support: Yes | Half duplex: Yes | Master (outer) case height: 400 mm | Warnings: Ensure the unit is adequately ventilated during operation. | Power supply included: Yes | Warnings: Do not open the case or try to repair it yourself. | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Mean time between failures (MTBF): 100000 h | Switch type: Unmanaged

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950