



Cudy GS1005P network switch Unmanaged Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Grey



Model: GS1005P

Manufacturer: CUDY

EAN: 6971690790998

Product Code: 200086

R854

Power connector: DC-in jack | Power over Ethernet plus (PoE+) ports quantity: 4 | MAC address table: 2048 entries | Forwarding rate: 7.44 Mpps | Switch type: Unmanaged | Flow control support: Yes | Uplink ports quantity: 1 | Warranty period: 1 year(s) | Rack mount kit: Yes | LED indicators: PoE | Copper ethernet cabling technology: 100BASE-TX | Copper ethernet cabling technology: 1000BASE-T | Power consumption (typical): 5 W | Package height: 81.5 mm | Copper ethernet cabling technology: 10BASE-T | Storage temperature (T-T): -40 - 70 °C | AC input voltage: 100 - 240 V | LED indicators: Link | LED indicators: Power | LED indicators: Activity | Input current: 1.25 A | Basic switching RJ-45 Ethernet ports quantity: 5 | Package depth: 123 mm | Cables included: DC | Package weight: 784 g |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

AC input frequency: 50/60 Hz | Operating relative humidity (H-H): 10 - 90% | Cables included: AC | Ethernet LAN data rates: 10,100,1000 Mbit/s | Height: 28 mm | User guide: Yes | Product colour: Grey | Package type: Box | Power over Ethernet (PoE): Yes | Width: 119 mm | Package width: 186 mm | Power source: DC | Housing material: Metal | Switching capacity: 10 Gbit/s | Weight: 261 g | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.3at | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Input voltage: 52 V | Networking standards: IEEE 802.3i | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.3u | Power supply included: Yes | Operating temperature (T-T): 0 - 40 °C | Power consumption (max): 60 W | Total Power over Ethernet (PoE) budget: 60 W | Depth: 85 mm | Plug and Play: Yes | Storage relative humidity (H-H): 10 - 95% | Warnings: Ensure the unit is adequately ventilated during operation. | Warnings: Do not open the case or try to repair it yourself. | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950