



Cudy GS105 network switch Unmanaged Gigabit Ethernet (10/100/1000) Black



Model: GS105

Manufacturer: CUDY

EAN: 6971690790431

Product Code: 200087

R361

Warnings: Do not open the case or try to repair it yourself. | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Warnings: Ensure the unit is adequately ventilated during operation. | Cable types supported: Cat6 | Cable types supported: Cat8.1 | Storage temperature (T-T): -40 - 70 °C | Cable types supported: Cat5 | Cable types supported: Cat5e | Cable types supported: Cat4 | Power over Ethernet (PoE): No | Cable types supported: Cat7 | Storage relative humidity (H-H): 5 - 90% | Master (outer) case height: 400 mm | Rack mounting: No | Cable types supported: Cat6a | Width: 86.5 mm | Store-and-forward: Yes | Forwarding rate: 7.44 Mpps | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Cable types supported: Cat3 | Power source: DC | Power consumption (max): 1.2 W | Copper ethernet cabling technology: 1000BASE-T | Switching capacity: 10 Gbit/s | Depth: 53 mm | Master (outer) case length: 320 mm | Power connector: DC-in

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

jack | Full duplex: Yes | Copper ethernet cabling technology: 100BASE-TX | Copper ethernet cabling technology: 10BASE-T | Height: 23 mm | Operating relative humidity (H-H): 10 - 90% | Master (outer) case width: 505 mm | Cable types supported: Cat6e | Cable types supported: Cat7e | VLAN support: Yes | DC input voltage: 5 V | Cable types supported: Cat8 | Cables included: DC | Basic switching RJ-45 Ethernet ports quantity: 5 | Cable types supported: Cat6+ | Products per master (outer) case: 40 pc(s) | Half duplex: Yes | MAC address table: 2048 entries | Mean time between failures (MTBF): 100000 h | Switch type: Unmanaged | Jumbo frames: 9000 | Manual: Yes | Jumbo frames support: Yes | Master (outer) case gross weight: 17 kg | Flow control support: Yes | Packet buffer memory: 0.125 MB | Power supply included: Yes | Networking standards: IEEE 802.3x | Operating temperature (T-T): 0 - 40 °C | Weight: 115.1 g | Networking standards: IEEE 802.3u | Product colour: Black | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | LED indicators: Loop | LED indicators: Power | Input current: 0.55 A | LED indicators: Link | Operating altitude: 0 - 3048 m | Ethernet LAN data rates: 10,100,1000 Mbit/s

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950