

Hikvision DS-3E0310HP-E network links Non-managed Fast Ethernet (10/100) PoE support Blue

Model: DS-3E0310HP-E

Manufacturer: HIKVISION

EAN: 6954273693350

Product Code: 200100

R1,941

Weight: 550 g | Product colour: Blue | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3bt | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.3at | LED indicators: Yes | Package weight: 1.22 kg | Networking standards: IEEE 802.3z | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Input current: 2.5 A | Switch type: Unmanaged | Power consumption (typical): 10 W | Operating temperature (T-T): -10 - 55 °C | Total Power over Ethernet (PoE) budget: 110 W | Power over Ethernet (PoE) power per port: 60 W | Storage relative humidity (H-H): 5 - 95% | Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100) | Operating relative humidity (H-H): 5 - 95% | Depth: 103.3 mm | Housing material: Metal | Power over Ethernet (PoE) ports quantity: 8 | Networking standards: IEEE 802.3u | Height: 27.8 mm | Full duplex:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Yes | Basic switching RJ-45 Ethernet ports quantity: 8 | Storage temperature (T-T): -40 - 85 °C | Store-and-forward: Yes | Power over Ethernet (PoE): Yes | 10G support: No | Power consumption (max): 120 W | Auto MDI/MDI-X: Yes | MAC address table: 16000 entries | Switching capacity: 5.6 Gbit/s | Width: 217.6 mm | Warnings: Ensure the unit is adequately ventilated during operation. | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Warnings: Do not open the case or try to repair it yourself. | Gigabit Ethernet (copper) ports quantity: 2 | DC input voltage: 48 V | Forwarding rate: 4.166 Mpps

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950