



Hikvision DS-3E0310HP-E network links Non-managed Fast Ethernet (10/100) PoE support Blue

Model: DS-3E0310HP-E

Manufacturer: HIKVISION

EAN: 6954273693350

Product Code: 200100

R1,965

Operating temperature (T-T): -10 - 55 °C | Total Power over Ethernet (PoE) budget: 110 W | Weight: 550 g | Switching capacity: 5.6 Gbit/s | Height: 27.8 mm | Package weight: 1.22 kg | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Operating relative humidity (H-H): 5 - 95% | Networking standards: IEEE 802.3u | Housing material: Metal | Networking standards: IEEE 802.3x | Storage temperature (T-T): -40 - 85 °C | Networking standards: IEEE 802.3af | Power consumption (max): 120 W | Full duplex: Yes | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.3bt | Auto MDI/MDI-X: Yes | Power over Ethernet (PoE) ports quantity: 8 | Store-and-forward: Yes | Basic switching RJ-45 Ethernet ports quantity: 8 | Power over Ethernet (PoE) power per port: 60 W | Power consumption (typical): 10 W | Networking standards: IEEE 802.3z |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Storage relative humidity (H-H): 5 - 95% | Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100) | Power over Ethernet (PoE): Yes | MAC address table: 16000 entries | LED indicators: Yes | Product colour: Blue | Switch type: Unmanaged | 10G support: No | Depth: 103.3 mm | Width: 217.6 mm | Input current: 2.5 A | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Warnings: Ensure the unit is adequately ventilated during operation. | Warnings: Do not open the case or try to repair it yourself. | DC input voltage: 48 V | Forwarding rate: 4.166 Mpps | Gigabit Ethernet (copper) ports quantity: 2

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950