



Mercusys MB110-4G wireless router Ethernet Single- band (2.4 GHz) White

Model: MB110-4G

Manufacturer: MERCUSYS

EAN: 6957939001995

Product Code: 200117

R1,334

Product type: Desktop/pole router | Width: 90 mm | 3G standards: UMTS | Height: 150.5 mm | Reset button: Yes | 3G standards: HSPA+ | Quick installation guide: Yes | Output voltage: 9 V | Top Wi-Fi standard: Wi-Fi 4 (802.11n) | DC-in jack: Yes | USB port: No | WLAN data transfer rate (max): 300 Mbit/s | Number of products included: 1 pc(s) | 4G standard: LTE-TDD & LTE-FDD | SIM card slot: Yes | Ethernet LAN interface type: Ethernet | Wi-Fi standards: 802.11g | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Wi-Fi standards: Wi-Fi 4 (802.11n) | DHCP server: Yes | Dual SIM support: No | Security algorithms: WPA2-PSK | WAN connection type: RJ-45 | Security algorithms: WPA | System event log: Yes | Operating temperature (T-T): 0 - 40 °C | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | Operating relative humidity (H-H): 10 - 90% | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Ethernet LAN: Yes | Cabling technology: 10/100Base-T(X) | Ethernet LAN data rates: 100 | Ethernet LAN (RJ-45) ports: 2 |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Universal Plug and Play (UPnP): Yes | Wi-Fi band: Single-band (2.4 GHz) | Storage temperature (T-T): -40 - 70 °C | Output current: 0.85 A | Package type: Box | Weight: 710 g | Product colour: White | AC adapter included: Yes | 3G standards: HSPA | Networking standards: IEEE 802.11b | Ethernet WAN: Yes | Wi-Fi standards: 802.11b | Power source type: DC | Wi-Fi Multimedia (WMM)/(WME): Yes | Firmware upgradeable: Yes | Ethernet LAN data rates: 10 | Security algorithms: 128-bit WEP | Depth: 92 mm | DSL WAN: No | SIM card type: NanoSIM | 3G bands supported: 850 | 3G bands supported: 900 | 3G bands supported: 2100 | Indication light: Yes | 4G bands supported: 900 | 4G bands supported: 2100 | 4G bands supported: 800 | Antenna design: Internal | 4G bands supported: 2600 | 4G bands supported: 850 | 4G bands supported: 2500 MHz | 4G bands supported: 700 | 4G bands supported: 2300 | 4G bands supported: 1800 | Port triggering: Yes | 3G/4G USB modem compatibility: Yes | Port forwarding: Yes | WPS push button: Yes | Mobile network generation: 4G | Firewall: Yes | VoIP protocols: IPv4, IPv6 | Port-based Network Access Control (PNAC): Yes | Dynamic DNS (DDNS): Yes | DMZ support: Yes | Warnings: Do not expose the device to extreme temperatures. | Warnings: Do not dismantle the unit yourself, there is a risk of electric shock. | Warnings: Do not expose the device to water or moisture.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950