



## **Mercusys MB110-4G wireless router Ethernet Single- band (2.4 GHz) White**

Model: MB110-4G

Manufacturer: MERCUSYS

EAN: 6957939001995

Product Code: 200117

## **R861**

SIM card slot: Yes | Wi-Fi Multimedia (WMM)/(WME): Yes | Power source type: DC | Output voltage: 9 V | Operating temperature (T-T): 0 - 40 °C | Ethernet LAN interface type: Ethernet | Package type: Box | Reset button: Yes | 3G standards: HSPA+ | 3G standards: UMTS | Output current: 0.85 A | System event log: Yes | 3G standards: HSPA | Depth: 92 mm | Ethernet WAN: Yes | Ethernet LAN: Yes | Operating relative humidity (H-H): 10 - 90% | Ethernet LAN data rates: 100 Mbit/s | DSL WAN: No | Universal Plug and Play (UPnP): Yes | Top Wi-Fi standard: Wi-Fi 4 (802.11n) | Wi-Fi band: Single-band (2.4 GHz) | DHCP server: Yes | Ethernet LAN (RJ-45) ports: 2 | Dual SIM support: No | Width: 90 mm | Security algorithms: WPA | Security algorithms: 128-bit WEP | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | WAN connection type: RJ-45 | Networking standards: IEEE 802.11b | Quick installation guide: Yes | DC-in jack: Yes | USB port: No | Number of products included: 1 pc(s) | 4G standard: LTE-

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

TDD & LTE-FDD | Security algorithms: WPA2-PSK | Product type: Desktop/pole router | WLAN data transfer rate (max): 300 Mbit/s | Storage temperature (T-T): -40 - 70 °C | Firmware upgradeable: Yes | Ethernet LAN data rates: 10 | Product colour: White | AC adapter included: Yes | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Height: 150.5 mm | Cabling technology: 10/100Base-T(X) | Wi-Fi standards: 802.11b | Wi-Fi standards: 802.11g | Weight: 710 g | Wi-Fi standards: Wi-Fi 4 (802.11n) | Warnings: Do not expose the device to water or moisture. | Warnings: Do not expose the device to extreme temperatures. | Warnings: Do not dismantle the unit yourself, there is a risk of electric shock. | 4G bands supported: 700 | 4G bands supported: 2300 MHz | 4G bands supported: 900 | VoIP protocols: IPv4, IPv6 | 4G bands supported: 2600 | 4G bands supported: 850 | 4G bands supported: 2500 | Port-based Network Access Control (PNAC): Yes | 4G bands supported: 2100 | 4G bands supported: 800 | 4G bands supported: 1800 | Port triggering: Yes | DMZ support: Yes | Dynamic DNS (DDNS): Yes | Mobile network generation: 4G | Firewall: Yes | Port forwarding: Yes | SIM card type: NanoSIM | 3G bands supported: 2100 | 3G bands supported: 850 | Indication light: Yes | 3G/4G USB modem compatibility: Yes | WPS push button: Yes | 3G bands supported: 900 MHz | Antenna design: Internal

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950