



Tenda Nova MW5s 1200 Mbit/s White Power over Ethernet (PoE)

Model: MW5s 3pack

Manufacturer: TENDA

EAN: 6932849428063

Product Code: 200151

R2,793

Certification: FCC, CE, RoHS, EAC, IC | VPN support: IPsec pass through, PPTP pass through, L2TP pass through | Compatible operating systems: Android 4.0+, iOS 8+ | Depth: 91 mm | Antenna type: Internal | Power over Ethernet (PoE): Yes | Width: 91 mm | DC-in jack: Yes | Reset button: Yes | Operating relative humidity (H-H): 10 - 90% | Firmware upgradeable: Yes | Ethernet LAN data rates: 10 | Ethernet LAN data rates: 100 Mbit/s | Networking standards: IEEE 802.11v | Networking standards: IEEE 802.11b | Maximum data transfer rate (2.4 GHz): 300 Mbit/s | Service Set Identifier (SSID) features: SSID broadcast | DHCP server: Yes | Product colour: White | AC adapter included: Yes | Universal Plug and Play (UPnP): Yes | DHCP client: Yes | Firewall security: UDP flood attack defence, TCP flood attack defence, ICMP flood attack defence | Ethernet LAN data rates: 1000 Mbit/s | Maximum data transfer rate: 1200 Mbit/s | Operating temperature (T-T): 0 - 40 °C | LED indicators: Signal strength | Placement: Table | Package type: Box | Antenna features: Integrated antenna | Maximum data transfer rate (5 GHz): 867 Mbit/s | Networking standards: IEEE 802.11k | Networking

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

standards: IEEE 802.3u | Networking standards: IEEE 802.11ac | Storage relative humidity (H-H): 5 - 90% | Antenna direction type: Omni-directional | Networking standards: IEEE 802.11r | Security algorithms: WPA2-PSK | Output current: 1 A | AC input voltage: 100 - 240 V | Quantity per pack: 3 pc(s) | 5 GHz: Yes | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.11a | Antennas quantity: 2 | Ethernet LAN (RJ-45) ports: 2 | MIMO: Yes | Storage temperature (T-T): -40 - 70 °C | MIMO type: Multi User MIMO | Cables included: LAN (RJ-45) | 2.4 GHz: Yes | Input current: 0.6 A | Height: 93 mm | WAN connection: Ethernet (RJ-45) | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | AC input frequency: 50 - 60 Hz | LED indicators: System | Antenna gain level (max): 3 dBi | Output voltage: 12 V

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950