

Tenda TX12 PRO wireless router Fast Ethernet Dual-band (2.4 GHz 5 GHz) Black

Tenda TX12 PRO wireless router Fast Ethernet Dual-band (2.4 GHz 5 GHz) Black



Model: TX12 PRO

Manufacturer: TENDA

EAN: 6932849426984

Product Code: 200164

R1,509

Ethernet LAN interface type: Fast Ethernet | DSL WAN: No | Ethernet LAN data rates: 1000 Mbit/s | SSID-based VLAN assignment: Yes | Ethernet LAN data rates: 100 | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | Wi-Fi standards: Wi-Fi 4 (802.11n) | WAN connection type: RJ-45 | Wi-Fi standards: Wi-Fi 6 (802.11ax) | Antennas quantity: 5 | Dynamic DNS (DDNS): Yes | Width: 267 mm | Product type: Tabletop router | Port forwarding: Yes | Output voltage: 12 V | WLAN data transfer rate (first band): 574 Mbit/s | WLAN data transfer rate (second band): 2402 Mbit/s | Ethernet LAN data rates: 10 | DMZ support: Yes | DHCP server: Yes | WPS push button: Yes | Depth: 166 mm | Wi-Fi standards: 802.11g | Output current: 1.5 A | Filtering: Yes | WLAN data transfer rate (max): 2402 Mbit/s | DHCP client: Yes | Product colour: Black | Ethernet WAN: Yes | MIMO: Yes | Security algorithms: WPS | USB port: No | Security algorithms: WPA-PSK | 3G/4G USB modem compatibility: No | AC input voltage: 100 - 240 V | Maximum Tx power (2.4 GHz): 20 dBmW | Web-based management: Yes | Antenna gain level (max):

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

6 dBi | Ethernet LAN: Yes | SIM card slot: No | Security algorithms: WPA | Security algorithms: WPA3-
SAE | Operating temperature (T-T): 0 - 40 °C | Power source type: AC | Universal Plug and Play
(UPnP): Yes | Cables included: LAN (RJ-45) | Antenna design: External | LED indicators: System |
Security algorithms: WPA2-PSK | Top Wi-Fi standard: Wi-Fi 6 (802.11ax) | Ethernet LAN (RJ-45) ports:
3 | Height: 222 mm | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Wi-Fi standards: 802.11b | AC input
frequency: 50 - 60 Hz | Storage temperature (T-T): -40 - 70 °C | MU-MIMO technology: Yes | VPN
server: PPTP Client PPTP Server L2TP Client PPTP Pass Through L2TP Pass Through IPsec Pass
Through | AC adapter included: Yes | Maximum Tx power (5 GHz): 23 dBmW | WAN ports quantity: 1 |
Warnings: Avoid contact with liquids as this may cause electric shock. | Warnings: The product may
emit radio waves that may interfere with other electronic devices. | Warnings: Do not open the
appliance housing - risk of electric shock. | Compliance certificates: Federal Communications
Commission (FCC) | Compliance certificates: RoHS | Compliance certificates: CE

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices
may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or
typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950