



Teltonika RUT950 wireless router Fast Ethernet Single- band (2.4 GHz) 4G Black

Model: RUT950U022C0

Manufacturer: TELTONIKA

EAN: 4779027311289

Product Code: 200179

R5,228

Certification: CE/RED, FCC, ISED (IC), EAC, RCM, PTCRB, RoHS, WEEE | Firewall: Yes | Operating temperature (T-T): -40 - 75 °C | Routing protocols: OSPF | Routing protocols: RIP-1 | Ethernet LAN (RJ-45) ports: 4 | Routing protocols: RIP-2 | Routing protocols: BGP | Top Wi-Fi standard: Wi-Fi 4 (802.11n) | SSID-based VLAN assignment: Yes | Output voltage: 9 - 30 V | Cables included: LAN (RJ-45) | WAN connection type: RJ-45 | UMTS bands supported: 2100 MHz | Mobile network generation: 4G | DoS attack prevention: Yes | Product type: Tabletop router | 3G/4G USB modem compatibility: No | DSL WAN: No | GSM bands supported: 900 | 4G: Yes | Power consumption (typical): 7 W | Detachable antenna(s): Yes | Manual: Yes | Indication light: Yes | Product colour: Black | AC input voltage: 100 - 240 V | AC input frequency: 50 - 60 Hz | 4G bands supported: 2100 | 4G bands supported: 800 | 4G bands supported: 2600 | Built-in processor: Yes | Firmware upgradeable: Yes |

Ethernet LAN data rates: 10 | VPN tunnels quantity: 4 | Width: 80 mm | Ethernet LAN data rates: 100

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

| Auto MDI/MDI-X: Yes | Operating relative humidity (H-H): 10 - 90% | UMTS bands supported: 900 | Antennas quantity: 4 | Antenna design: External | Load balancing system: Yes | Quick start guide: Yes | Wi-Fi standards: 802.11g | Height: 46 mm | GSM bands supported: 1800 | Mean time between failures (MTBF): 270000 h | Wi-Fi standards: Wi-Fi 4 (802.11n) | Networking standards: IEEE 802.3u | Security algorithms: 256-bit AES | USB port: No | 4G standard: LTE | Quality of Service (QoS) support: Yes | 4G bands supported: 900 | AC adapter included: Yes | 4G bands supported: 1800 | Networking standards: IEEE 802.3 | Security algorithms: 3DES | Security algorithms: WPA2-PSK | Security algorithms: WPA2 | Networking standards: IEEE 802.11b | Security algorithms: 128-bit AES | Security algorithms: 192-bit AES | Storage temperature (T-T): -45 - 80 °C | Web-based management: Yes | MAC address filtering: Yes | Security algorithms: WEP | Security algorithms: DES | Power source type: DC | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Storage relative humidity (H-H): 5 - 95% | WLAN data transfer rate (max): 150 Mbit/s | Harmonized System (HS) code: 85176990 | Short Message Service (SMS): Yes | Depth: 106 mm | SIM card slot: Yes | Ethernet LAN: Yes | Security algorithms: WPA-PSK | Dual SIM support: Yes | Wi-Fi standards: 802.11b | Filtering: Yes | Processor frequency: 550 MHz | 3G: Yes | Weight: 235 g | Reset button: Yes | 3G standards: HSPA+ | 3G standards: UMTS | System event log: Yes | Wi-Fi band: Single-band (2.4 GHz) | Ethernet LAN interface type: Fast Ethernet | Dynamic DNS (DDNS): Yes | Ethernet WAN: Yes | 2G standards: GSM

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950