

Teltonika RUT950 wireless router Fast Ethernet Single-band (2.4 GHz) 4G Black

Model: RUT950U022C0

Manufacturer: TELTONIKA

EAN: 4779027311289

Product Code: 200179

R5,228

Certification: CE/RED, FCC, ISED (IC), EAC, RCM, PTCRB, RoHS, WEEE | DSL WAN: No | Ethernet LAN data rates: 100 Mbit/s | Quality of Service (QoS) support: Yes | 4G bands supported: 900 | Wi-Fi band: Single-band (2.4 GHz) | UMTS bands supported: 2100 MHz | Storage temperature (T-T): -45 - 80 °C | Product colour: Black | Product type: Tabletop router | UMTS bands supported: 900 | Ethernet LAN: Yes | 4G bands supported: 2600 | 3G standards: UMTS | Built-in processor: Yes | WAN connection type: RJ-45 | AC input voltage: 100 - 240 V | AC adapter included: Yes | 4G bands supported: 1800 | Security algorithms: WPA2-PSK | Web-based management: Yes | MAC address filtering: Yes | Security algorithms: WEP | Security algorithms: DES | Security algorithms: WPA-PSK | Processor frequency: 550 MHz | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3u | Security algorithms: 256-bit AES | Networking standards: IEEE 802.11b | Security algorithms: 128-bit AES | Security algorithms: 192-bit AES | Wi-Fi standards: Wi-Fi 4 (802.11n) | USB port: No | Width: 80 mm |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Operating temperature (T-T): -40 - 75 °C | Routing protocols: OSPF | Firewall: Yes | Ethernet LAN (RJ-45) ports: 4 | Auto MDI/MDI-X: Yes | Routing protocols: BGP | Wi-Fi standards: 802.11b | Ethernet WAN: Yes | GSM bands supported: 900 | Height: 46 mm | VPN tunnels quantity: 4 | Antenna design: External | GSM bands supported: 1800 | Cables included: LAN (RJ-45) | 3G: Yes | Mobile network generation: 4G | Manual: Yes | Power source type: DC | Dual SIM support: Yes | 3G/4G USB modem compatibility: No | Reset button: Yes | 3G standards: HSPA+ | Firmware upgradeable: Yes | Ethernet LAN data rates: 10 | Routing protocols: RIP-1 | Power consumption (typical): 7 W | Depth: 106 mm | Security algorithms: 3DES | AC input frequency: 50 - 60 Hz | 4G bands supported: 2100 | 4G bands supported: 800 | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Storage relative humidity (H-H): 5 - 95% | WLAN data transfer rate (max): 150 Mbit/s | Routing protocols: RIP-2 | Quick start guide: Yes | Wi-Fi standards: 802.11g | Load balancing system: Yes | Weight: 235 g | Mean time between failures (MTBF): 270000 h | 2G standards: GSM | Harmonized System (HS) code: 85176990 | Short Message Service (SMS): Yes | 4G standard: LTE | Operating relative humidity (H-H): 10 - 90% | System event log: Yes | DoS attack prevention: Yes | Antennas quantity: 4 | Filtering: Yes | SIM card slot: Yes | Security algorithms: WPA2 | Detachable antenna(s): Yes | SSID-based VLAN assignment: Yes | 4G: Yes | Output voltage: 9 - 30 V | Top Wi-Fi standard: Wi-Fi 4 (802.11n) | Indication light: Yes | Ethernet LAN interface type: Fast Ethernet | Dynamic DNS (DDNS): Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950