CSSi SA - "Securing Tomorrow, Today"
Waterfall Office Park, 28 Augrabies Rd Vorna Valley, Midrand, 1685
Generated: 2026-10-30 12:35



TOTOLINK N300RT wireless router Fast Ethernet Single-band (2.4 GHz) Black, White

Model: N300RT

Manufacturer: TOTOLINK

EAN: 6952887400012

Product Code: 200183

R1,002

Receiver sensitivity: - 270M: -61 dBm@10% PER - 135M: -65 dBm@10% PER - 54M: -68 dBm@10% PER - 11M: -85 dBm@8% PER - 6M: -88 dBm@10% PER - 1M: -90 dBm@8% PER | Wi-Fi standards: 802.11g | Ethernet LAN data rates: 100 | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | DHCP client: Yes | Antenna gain level (max): 5 dBi | Output voltage: 9 V | Power consumption (typical): 4.5 W | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Security algorithms: WPA2-PSK | WPS push button: Yes | Power over Ethernet (PoE): No | Ethernet LAN: Yes | SIM card slot: No | Wi-Fi standards: Wi-Fi 4 (802.11n) | 4G: No | On/off switch: No | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | Memory card slot(s): No | Depth: 76 mm | Security algorithms: WPA | Product type: Tabletop router | Detachable antenna(s): No | WLAN data transfer rate (third band): 11 Mbit/s | Filtering: Yes | WLAN data transfer rate (first band): 300 Mbit/s | Top Wi-Fi standard: Wi-Fi 4 (802.11n) | Antennas quantity: 2 | 3G: No | WAN connection type:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

RJ-45 | DSL WAN: No | Security algorithms: 128-bit WEP | Firmware upgradeable: Yes | Ethernet LAN data rates: 10 | Cables included: LAN (RJ-45) | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Access Control List (ACL): Yes | Output current: 0.5 A | AC input voltage: 100 - 240 V | LED indicators: LAN, Power, WAN | Operating relative humidity (H-H): 10 - 90% | IP address filtering: Yes | Indication light: Yes | Width: 147.5 mm | URL filtering: Yes | Ethernet LAN interface type: Fast Ethernet | Port forwarding: Yes | Plug and Play: Yes | DMZ support: Yes | Power source type: DC | Wi-Fi standards: 802.11b | Parental control: Yes | Ethernet WAN: Yes | Web-based setup wizard: Yes | Built-in display: No | Networking standards: IEEE 802.11b | DC-in jack: Yes | Power supply: 4.5 W | WLAN data transfer rate (max): 300 Mbit/s | AC input frequency: 50 - 60 Hz | Operating temperature (T-T): 0 - 40 °C | Firewall: Yes | USB port: No | Universal Plug and Play (UPnP): Yes | Ethernet LAN (RJ-45) ports: 5 | Antenna design: External | Product colour: Black | Quick installation guide: Yes | Product colour: White | 3G/4G USB modem compatibility: No | Wi-Fi band: Single-band (2.4 GHz) | Reset button: Yes | Antenna included: Yes | Web-based management: Yes | MAC address filtering: Yes | Housing material: Acrylonitrile butadiene styrene (ABS), Plastic, Polycarbonate (PC) | DHCP server: Yes | Built-in processor: Yes | WLAN data transfer rate (second band): 54 Mbit/s | Height: 25 mm | AC adapter included: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950