



TP-Link Archer 5G AX1800 Wireless Dual- Band Gigabit Router



Model: ARCHER NX200

Manufacturer: TP-LINK

EAN: 8885020621075

Product Code: 200188

R5,911

VPN support: PPTP VPN, IPSec VPN , OpenVPN | 3G standards: UMTS | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | 3G standards: HSPA+ | 3G standards: HSPA | 3G standards: DC-HSDPA | 4G standard: LTE-TDD & LTE-FDD | 4G bands supported: 3700 MHz | 4G bands supported: 2600 | 4G bands supported: 850 | 4G bands supported: 2500 MHz | 4G bands supported: 2100 | 4G bands supported: 800 | 4G bands supported: 1800 | 5G bands supported: 2100 | Height: 99 mm | 5G bands supported: 850 | 4G bands supported: 1500 | 5G bands supported: 3500 | Output current: 2 A | 5G bands supported: 3700 | 4G bands supported: 900 | Access Control List (ACL): Yes | DMZ support: Yes | Dynamic DNS (DDNS): Yes | Port triggering: Yes | DHCP server: Yes | Firewall security: IPv4 SPI Firewall, IPv6 Firewall | WLAN data transfer rate (second band): 1201 Mbit/s | Firewall: Yes | 5G bands supported: 2500 | 4G bands supported: 700 | 4G bands supported: 2300 | 5G bands supported: 2600 | 5G bands supported: 800 | 5G bands supported: 900 | Browser supported: Internet Explorer 11, Firefox 12.0,

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Chrome 20.0, Safari 4.0, or other Java-enabled browser | Parental control: Yes | Depth: 190 mm | Supported network protocols: IPv4, IPv6 | Ethernet LAN: Yes | Product type: Tabletop router | 4G bands supported: 3500 | SIM card slot: Yes | 3G bands supported: 900 | Customs product code (TARIC): 8517620000 | Number of guest networks (5 GHz): 1 | WAN connection type: RJ-45 | MU-MIMO technology: Yes | Wi-Fi Multimedia (WMM)/(WME): Yes | USB port: No | On/off switch: Yes | 3G bands supported: 2100 | SIM card type: NanoSIM | Number of guest networks (2.4 GHz): 1 | 3G bands supported: 850 | WLAN data transfer rate (first band): 574 Mbit/s | 5G bands supported: 700 | 5G bands supported: 1800 | 5G bands supported: 2300 | WPS push button: Yes | Detachable antenna(s): Yes | DoS attack prevention: Yes | Antenna design: Internal | Mobile network generation: 5G | Linux operating systems supported: Yes | Compliance certificates: RoHS | Compliance certificates: CE | Warnings: Do not expose the device to extreme temperatures. | Warnings: Do not expose the device to water or moisture. | Warnings: Do not dismantle the unit yourself, there is a risk of electric shock. | Networking standards: IEEE 802.11b | Product colour: White | Networking standards: IEEE 802.11ac | Reset button: Yes | Security algorithms: WPA2-PSK | Security algorithms: 128-bit WEP | Wi-Fi standards: 802.11a | Wi-Fi standards: Wi-Fi 6 (802.11ax) | Wi-Fi standards: 802.11g | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Networking standards: IEEE 802.11a | Networking standards: IEEE 802.11ax | DHCP client: Yes | Package width: 230 mm | Wi-Fi standards: Wi-Fi 4 (802.11n) | Ethernet LAN interface type: Gigabit Ethernet | Weight: 610 g | Package height: 221 mm | AC input voltage: 100 - 240 V | Antennas quantity: 10 | Ethernet WAN: Yes | Ethernet LAN data rates: 10 | Windows operating systems supported: Windows 10 | WLAN data transfer rate (max): 1800 Mbit/s | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Windows operating systems supported: Windows 7 | Windows operating systems supported: Windows XP | Windows operating systems supported: Windows 8 | Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows Vista | Ethernet LAN data rates: 100 | AC input frequency: 50/60 Hz | Security algorithms: WPA | Power source type: AC | Operating temperature (T-T): 0 - 40 °C | Operating relative humidity (H-H): 10 - 90% | Ethernet LAN data rates: 1000 Mbit/s | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Windows operating systems supported: Windows 98SE | Package depth: 115 mm | Quick installation guide: Yes | AC adapter included: Yes | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | Mac operating systems supported: Yes | Ethernet LAN (RJ-45) ports: 3 | Width: 99 mm | Wi-Fi standards: 802.11b | Windows operating systems supported: Windows 2000 | Top Wi-Fi standard: Wi-Fi 6 (802.11ax) | Cables included: LAN (RJ-45) | Package weight: 1.19 kg | Windows operating systems supported: Windows NT | Output voltage: 12 V

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950