



TP-Link TL- WR802N wireless router Fast Ethernet Single-band (2.4 GHz) Blue, White

Model: TL-WR802N

Manufacturer: TP-LINK

EAN: 6935364071714

Product Code: 200190

R576

Filtering: Yes | LED indicators: Activity, LAN, Power, WLAN | Reset button: Yes | Product colour: White
| AC adapter included: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS)
support: Yes | Product colour: Blue | Stateful Packet Inspection (SPI): Yes | Processor cores: 1 |
Operating relative humidity (H-H): 10 - 90% | Operating temperature (T-T): 0 - 40 °C | DHCP client:
Yes | DC-in jack: Yes | Package weight: 240 g | Ethernet LAN data rates: 100 Mbit/s | Security
algorithms: WPA-Enterprise | Networking standards: IEEE 802.11g | Networking standards: IEEE
802.11n | Security algorithms: WPA2 | Security algorithms: WPA2-Enterprise | Web-based
management: Yes | MAC address filtering: Yes | Security algorithms: WEP | Ethernet LAN data rates:
10 | Networking standards: IEEE 802.11b | Security algorithms: WPA | Power source type: USB |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Ethernet LAN (RJ-45) ports: 1 | Warnings: Avoid contact with liquids as this may cause electric shock. | Warnings: The product may emit radio waves that may interfere with other electronic devices. | Warnings: Do not open the appliance housing - risk of electric shock. | Compliance certificates: Federal Communications Commission (FCC) | Wi-Fi standards: 802.11g | Output voltage: 5 V | Wi-Fi standards: 802.11b | Windows operating systems supported: Windows 7 Home Basic x64 | Windows operating systems supported: Windows 98SE | Universal Plug and Play (UPnP): Yes | Windows operating systems supported: Windows 7 Home Premium x64 | Windows operating systems supported: Windows 7 Enterprise x64 | On/off switch: Yes | Windows operating systems supported: Windows Vista Enterprise | Windows operating systems supported: Windows 8.1 Enterprise | Windows operating systems supported: Windows 7 Professional | Cabling technology: 10/100Base-T(X) | Windows operating systems supported: Windows 8 x64 | Windows operating systems supported: Windows Vista Business x64 | Windows operating systems supported: Windows XP Professional | Windows operating systems supported: Windows Vista Business | Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows Vista Ultimate | Windows operating systems supported: Windows 7 Ultimate x64 | Windows operating systems supported: Windows Vista Home Premium | Windows operating systems supported: Windows XP Home | Windows operating systems supported: Windows 7 Starter x64 | Windows operating systems supported: Windows NT | Windows operating systems supported: Windows Vista Home Basic | Windows operating systems supported: Windows 8 | Cables included: USB | Windows operating systems supported: Windows 8 Enterprise | Windows operating systems supported: Windows 7 Home Basic | Windows operating systems supported: Windows 7 Ultimate | Windows operating systems supported: Windows 2000 | Windows operating systems supported: Windows 8 Pro x64 | Windows operating systems supported: Windows 8.1 Pro | Windows operating systems supported: Windows 7 Home Premium | Windows operating systems supported: Windows 7 Starter | Windows operating systems supported: Windows Vista Enterprise x64 | Windows operating systems supported: Windows 8.1 Enterprise x64 | Windows operating systems supported: Windows 8.1 Pro x64 | Windows operating systems supported: Windows 8.1 x64 | VPN Passthrough: Yes | Windows operating systems supported: Windows Vista Home Premium x64 | Windows operating systems supported: Windows XP Home x64 | Cables included: LAN (RJ-45) | Firewall security: SPI | Windows operating systems supported: Windows Vista Home Basic x64 | Windows operating systems supported: Windows 7 Professional x64 | Height: 18 mm | Wi-Fi standards: Wi-Fi 4 (802.11n) | Top Wi-Fi standard: Wi-Fi 4 (802.11n) | DHCP server: Yes | WAN connection type: RJ-45 | Firewall: Yes | Mac operating systems supported: MacOS | DoS attack prevention: Yes | Package height: 73.5 mm | Depth: 57 mm |

Antennas quantity: 2 | Output current: 1 A | IP address filtering: Yes | Linux operating systems

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

supported: Yes | Supported network protocols: IPv4, IPv6 | Memory card slot(s): No | Ethernet LAN: Yes | SIM card slot: No | Port forwarding: Yes | Windows operating systems supported: Windows Vista Ultimate x64 | Windows operating systems supported: Windows 8 Enterprise x64 | Windows operating systems supported: Windows 8 Pro | Windows operating systems supported: Windows 7 Enterprise | 3G/4G USB modem compatibility: No | Ethernet WAN: Yes | Port triggering: Yes | Built-in processor: Yes | Storage relative humidity (H-H): 5 - 90% | Antenna design: Internal | Windows operating systems supported: Windows XP Professional x64 | Product type: Portable router | DMZ support: Yes | DSL WAN: No | Dynamic DNS (DDNS): Yes | Package depth: 109 mm | Quick installation guide: Yes | Ethernet LAN interface type: Fast Ethernet | Transmit power: CE: , 20dBm(2.4GHz) , FCC: , 30dBm | USB port: Yes | Number of guest networks (2.4 GHz): 1 | Wi-Fi band: Single-band (2.4 GHz) | Package width: 110 mm | Harmonized System (HS) code: 85176990 | Sustainability compliance: Yes | Width: 57 mm | WLAN data transfer rate (max): 300 Mbit/s

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950