



TP-Link AC1200 Wireless Dual Band WiFi Router



Model: C50

Manufacturer: TP-LINK

EAN: 6935364081065

Product Code: 200191

R689

Receiver sensitivity: 5GHz: 11a 54M: -76dBm 11ac VHT20 MCS8: -70dBm 11ac VHT40 MCS9: -65.5dBm 11ac VHT80 MCS9: -61.5dBm 2.4GHz: 11g 54M: -76dBm 11n HT20 MCS7: -74dBm 11n HT40 MCS7: | Certification: CE, FCC, RoHS | LED indicators: LAN, Link, Power, WLAN | Windows operating systems supported: Windows 8 | Windows operating systems supported: Windows 8.1 | Wall mountable: Yes | Operating temperature (T-T): 0 - 40 °C | VoIP protocols: IPv4 / IPv6 | Operating relative humidity (H-H): 10 - 90% | Output current: 0.85 A | AC input voltage: 220 - 240 V | Width: 230 mm | Access Control List (ACL): Yes | DSL WAN: No | WAN connection type: RJ-45 | Reset button: Yes | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | USB port: No | Ethernet LAN (RJ-45) ports: 4 | Package width: 290 mm | WLAN data transfer rate (first band): 867 Mbit/s | DoS attack prevention: Yes | Mac operating systems supported: MacOS | Package depth: 240 mm | Windows operating systems supported: Windows NT | Static route: Yes | VPN Passthrough: Yes | Height: 35 mm | Storage temperature (T-T): -40 - 70 °C | Ethernet WAN: Yes | Cables included: LAN (RJ-45) | Universal Plug and Play (UPnP): Yes | Windows operating systems supported: Windows 10 | Windows operating systems supported: Windows 8 Enterprise x64 | 3G/4G USB modem compatibility: No | Top Wi-Fi

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

standard: Wi-Fi 5 (802.11ac) | Package weight: 670 g | Windows operating systems supported: Windows 98SE | Product type: Tabletop router | Output voltage: 9 V | Ethernet LAN: Yes | SIM card slot: No | 4G: No | Mac compatibility: Yes | Depth: 144 mm | IP address filtering: Yes | On/off switch: Yes | Receive power: 23 dBmW | Indication light: Yes | Wi-Fi standards: 802.11g | Detachable antenna(s): Yes | Wi-Fi standards: 802.11a | 3G: No | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Windows operating systems supported: Windows XP | AC adapter included: Yes | Antennas quantity: 4 | Quick installation guide: Yes | Cabling technology: 10/100Base-T(X) | WLAN data transfer rate (second band): 300 Mbit/s | Antenna gain level (max): 76 dBi | Wi-Fi standards: Wi-Fi 4 (802.11n) | Harmonized System (HS) code: 85176990 | Firewall: Yes | Security algorithms: WPA2-PSK | WLAN data transfer rate (max): 867 Mbit/s | Security algorithms: WPA | Security algorithms: 128-bit WEP | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | WPS push button: Yes | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Transmit power: CE: 20dBm(2.4GHz), 23dBm(5GHz), FCC: 30dBm | Housing material: Plastic | Package height: 76 mm | Ethernet LAN interface type: Fast Ethernet | Windows operating systems supported: Windows 2000 | Wi-Fi standards: 802.11b | Package type: Box | DMZ support: Yes | DHCP server: Yes | Dynamic DNS (DDNS): Yes | Power source type: AC | Memory card slot(s): No | Port forwarding: Yes | Firewall security: DoS, SPI Firewall IP Address Filter / MAC Address Filter / Domain Filter IP and MAC Address Binding | Linux operating systems supported: Yes | Antenna design: External | Stateful Packet Inspection (SPI): Yes | DHCP client: Yes | Product colour: White | Ethernet LAN data rates: 100 Mbit/s | AC input frequency: 50 - 60 Hz | Filtering: Yes | Ethernet LAN data rates: 10 | DC-in jack: Yes | Networking standards: IEEE 802.11ac | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Web-based management: Yes | MAC address filtering: Yes | Networking standards: IEEE 802.11b | Networking standards: IEEE 802.11a | Warnings: The product may emit radio waves that may interfere with other electronic devices. | Warnings: Avoid contact with liquids as this may cause electric shock. | Warnings: Do not open the appliance housing - risk of electric shock.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950