



TP-Link AC1200 Wireless VDSL/ADSL Modem Router



Model: ARCHER VR300

Manufacturer: TP-LINK

EAN: 6935364081942

Product Code: 200200

R1,174

Certification: CE, RoHS, RCM | Output voltage: 12 V | Cables included: Phone (RJ-11) | USB port: No | Output current: 1 A | Height: 290 mm | ADSL2+: Yes | Mac operating systems supported: Yes | 4G: No | ADSL2: Yes | Universal Plug and Play (UPnP): Yes | Product type: Tabletop router | Windows operating systems supported: Yes | VPN Passthrough: Yes | DSL WAN: Yes | Mac compatibility: Yes | Top Wi-Fi standard: Wi-Fi 5 (802.11ac) | 3G/4G USB modem compatibility: No | Wi-Fi standards: 802.11a | ADSL: Yes | Cables included: LAN (RJ-45) | Antennas quantity: 4 | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Equivalent Isotropically Radiated Power (EIRP) (@IEEE 802.11b): 20 dBmW | Package depth: 240 mm | RJ-11 ports quantity: 1 | AC adapter included: Yes | Linux operating systems supported: Yes | Depth: 76 mm | Wi-Fi standards: 802.11g | Wi-Fi standards: 802.11b | Package weight: 840 g | VDSL2: Yes | Equivalent Isotropically Radiated Power (EIRP) (@IEEE 802.11n): 20 dBmW | Width: 385 mm | Storage relative humidity (H-H): 5 - 90% | Harmonized System (HS) code: 85176990 | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Ethernet LAN: Yes | SIM card slot: No | Operating relative humidity (H-H): 10 - 90% | 3G: No | On/off switch: Yes | Equivalent Isotropically Radiated Power (EIRP) (@IEEE 802.11g): 20 dBmW | Wi-Fi standards:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Wi-Fi 4 (802.11n) | WLAN data transfer rate (second band): 867 Mbit/s | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | Package width: 330 mm | WLAN data transfer rate (first band): 300 Mbit/s | Operating temperature (T-T): 0 - 40 °C | Ethernet LAN (RJ-45) ports: 4 | Firewall: Yes | Ethernet WAN: Yes | DHCP server: Yes | Dynamic DNS (DDNS): Yes | DMZ support: Yes | Ethernet LAN interface type: Fast Ethernet | Package height: 76 mm | WLAN data transfer rate (max): 867 Mbit/s | WPS push button: Yes | Antenna design: External | Ethernet LAN data rates: 10 | Ethernet LAN data rates: 100 Mbit/s | Quick start guide: Yes | Network address translation (NAT): Yes | Reset button: Yes | Filtering: Yes | Product colour: Black | Warnings: Do not open the appliance housing - risk of electric shock. | DHCP client: Yes | Warnings: Avoid contact with liquids as this may cause electric shock. | Warnings: The product may emit radio waves that may interfere with other electronic devices. | Security algorithms: IPSec | Security algorithms: WPA | Web-based management: Yes | MAC address filtering: Yes | Security algorithms: WEP | Networking standards: IEEE 802.11ac | Networking standards: IEEE 802.11a | Security algorithms: WPA2-PSK | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11b | Security algorithms: WPA-PSK | Security algorithms: WPA2 | Networking standards: IEEE 802.11h

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950