



TP-Link Archer AX5400 Dual- Band Gigabit Wi- Fi 6 Router, Black

Model: Archer AX73

Manufacturer: TP-LINK

EAN: 6935364010263

Product Code: 200201

R2,879

Packaging content: 1 x TP-Link Archer AX5400 Dual-Band Gigabit Wi-Fi 6 Router, Black | Wi-Fi standards: 802.11a | Antennas quantity: 6 | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: RoHS | Compliance certificates: CE | Universal Plug and Play (UPnP): Yes | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | WLAN data transfer rate (first band): 4804 Mbit/s | IP address filtering: Yes | DoS attack prevention: Yes | Depth: 147.2 mm | Output current: 2.5 A | Supported network protocols: IPv4, IPv6 | Built-in FTP server: Yes | Port triggering: Yes | Parental control: Yes | Media server: Yes | WAN connection type: RJ-45 | Antenna design: External | DMZ support: Yes | Ethernet LAN: Yes | SIM card slot: No | Access Control List (ACL): Yes | Height: 49.2 mm | Support Samba (storage): Yes | Output voltage: 12 V | Port forwarding: Yes | Product type: Portable router | WLAN data transfer rate (second band): 574 Mbit/s | Built-in processor: Yes | USB port: Yes | Width: 272.5 mm | Harmonized System (HS) code: 85176990 | Firewall: Yes | Ethernet LAN interface type: Gigabit Ethernet | Dynamic DNS (DDNS): Yes | DSL WAN:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

No | WPS push button: Yes | 3G/4G USB modem compatibility: No | Cabling technology: 10/100/1000Base-T(X) | On/off switch: Yes | Warnings: The product may emit radio waves that may interfere with other electronic devices. | Warnings: Avoid contact with liquids as this may cause electric shock. | Warnings: Do not open the appliance housing - risk of electric shock. | MU-MIMO technology: Yes | Number of guest networks (5 GHz): 1 | Sustainability compliance: Yes | Number of guest networks (2.4 GHz): 1 | Operating temperature (T-T): 0 - 40 °C | Modulation: 1024-QAM | Product colour: Black | Quick installation guide: Yes | Firmware upgradeable: Yes | Ethernet LAN data rates: 10 | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Modulation: OFDM | Processor frequency: 1500 MHz | Package weight: 800 g | Ethernet LAN data rates: 100 Mbit/s | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Wi-Fi standards: 802.11g | AC adapter included: Yes | Stateful Packet Inspection (SPI): Yes | Ethernet LAN (RJ-45) ports: 4 | DHCP client: Yes | Package depth: 310 mm | Ethernet LAN data rates: 1000 | Quantity per pack: 1 pc(s) | Security algorithms: WPA3 | Storage relative humidity (H-H): 5 - 90% | Wi-Fi standards: 802.11b | Security algorithms: WPA-Enterprise | Networking standards: IEEE 802.11g | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 1 | Networking standards: IEEE 802.11ax | Security algorithms: WPA | WLAN data transfer rate (max): 5400 Mbit/s | Reset button: Yes | Processor cores: 3 | Top Wi-Fi standard: Wi-Fi 6 (802.11ax) | Operating relative humidity (H-H): 10 - 90% | Networking standards: IEEE 802.11ac | Networking standards: IEEE 802.11a | Package height: 38 mm | Web-based management: Yes | MAC address filtering: Yes | Security algorithms: WPA2 | Security algorithms: WPA2-Enterprise | Cables included: LAN (RJ-45) | Package width: 124 mm | Network address translation (NAT): Yes | Networking standards: IEEE 802.11b | Filtering: Yes | Wi-Fi standards: Wi-Fi 4 (802.11n) | Ethernet WAN: Yes | Power source type: DC

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950