



TP-Link Archer AX1800 Dual- Band Wi-Fi 6 Router



Model: Archer AX23

Manufacturer: TP-LINK

EAN: 4897098687048

Product Code: 200204

R1,249

NAT functionality: Port Forwarding, Port Triggering, UPnP, DMZ | Certification: FCC, CE, RoHS | Wi-Fi standards: 802.11g | Wi-Fi standards: 802.11a | Wi-Fi standards: Wi-Fi 6 (802.11ax) | Processor frequency: 1500 MHz | WLAN data transfer rate (second band): 1201 Mbit/s | Wi-Fi standards: 802.11b | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Ethernet LAN: Yes | Ethernet LAN (RJ-45) ports: 4 | DC-in jack: Yes | Wi-Fi standards: Wi-Fi 4 (802.11n) | DMZ support: Yes | DHCP server: Yes | Access Control List (ACL): Yes | Guest access: Yes | Reset button: Yes | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | Operating relative humidity (H-H): 10 - 90% | Ethernet LAN interface type: Gigabit Ethernet | Dynamic DNS (DDNS): Yes | URL filtering: Yes | IP address filtering: Yes | SIM card slot: No | Antenna connector type: SMA | Warranty card: Yes | Static route: Yes | Depth: 135 mm | System event log: Yes | 4G: Yes | Output voltage: 12 V | Package width: 500 mm | Flow control support: Yes | DHCP client: Yes | Product colour: Black | Bandwidth control: Yes | Ethernet LAN data rates: 100 Mbit/s | AC adapter included: Yes | Ethernet LAN data rates: 10 | Quick installation guide: Yes | Package weight: 730 g | Windows operating systems supported: Windows Vista Enterprise | Windows operating

systems supported: Windows 8.1 Enterprise | Windows operating systems supported: Windows 7

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Professional | Windows operating systems supported: Windows 7 | Windows operating systems supported: Windows Vista Home Premium | Windows operating systems supported: Windows XP Home | Windows operating systems supported: Windows 10 Home | Windows operating systems supported: Windows 7 Starter x64 | Height: 41.6 mm | Windows operating systems supported: Windows 7 Home Basic | Windows operating systems supported: Windows 7 Ultimate | Windows operating systems supported: Windows 2000 | WAN connection type: RJ-45 | Windows operating systems supported: Windows 10 Enterprise | Windows operating systems supported: Windows 7 Home Basic x64 | Windows operating systems supported: Windows 98SE | Windows operating systems supported: Windows Vista Business | Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows Vista Ultimate | Windows operating systems supported: Windows 7 Ultimate x64 | Windows operating systems supported: Windows Vista | Windows operating systems supported: Windows 7 x64 | Windows operating systems supported: Windows 10 Pro x64 | Windows operating systems supported: Windows 8 Enterprise | Antenna design: External | Windows operating systems supported: Windows Vista Enterprise x64 | Windows operating systems supported: Windows 8.1 Enterprise x64 | Windows operating systems supported: Windows 8.1 Pro x64 | Windows operating systems supported: Windows 8.1 x64 | Windows operating systems supported: Windows 2000 Professional | Full duplex: Yes | Windows operating systems supported: Windows Vista Home Basic | Windows operating systems supported: Windows 10 Home x64 | Windows operating systems supported: Windows 8 | Windows operating systems supported: Windows 10 Enterprise x64 | Windows operating systems supported: Windows 8 Pro x64 | Windows operating systems supported: Windows 8.1 Pro | Windows operating systems supported: Windows 10 Pro | Windows operating systems supported: Windows 7 Home Premium | Windows operating systems supported: Windows 7 Starter | Windows operating systems supported: Windows 10 IoT Enterprise | Product type: Tabletop router | Port forwarding: Yes | Windows operating systems supported: Windows Vista Home Premium x64 | Windows operating systems supported: Windows 10 Education x64 | Windows operating systems supported: Windows XP Home x64 | Cables included: LAN (RJ-45) | Universal Plug and Play (UPnP): Yes | Operating temperature (T-T): 0 - 40 °C | Package height: 395 mm | Windows operating systems supported: Windows 7 Home Premium x64 | Windows operating systems supported: Windows 7 Enterprise x64 | Windows operating systems supported: Windows Vista x64 | Network address translation (NAT): Yes | Processor cores: 2 | Top Wi-Fi standard: Wi-Fi 6 (802.11ax) | Output current: 1 A | Harmonized System (HS) code: 85176990 | Package depth: 350 mm | Windows operating systems supported: Windows Vista Home Basic x64 | Windows operating systems supported: Windows 7 Professional x64 | Windows operating systems supported: Windows 8 x64 | Windows operating systems supported: Windows Vista Business x64 |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Windows operating systems supported: Windows 10 Education | Windows operating systems supported: Windows XP Professional | Windows operating systems supported: Windows XP | WLAN data transfer rate (first band): 574 Mbit/s | Built-in processor: Yes | Ethernet WAN: Yes | Width: 260.2 mm | USB port: No | Web-based setup wizard: Yes | Windows operating systems supported: Windows 10 | Windows operating systems supported: Windows Vista Ultimate x64 | Windows operating systems supported: Windows 10 IOT Core | Windows operating systems supported: Windows 8 Enterprise x64 | Windows operating systems supported: Windows 8 Pro | Windows operating systems supported: Windows 7 Enterprise | Ethernet LAN data rates: 1000 | Windows operating systems supported: Windows XP Professional x64 | Power source type: DC | Mac operating systems supported: Yes | Linux operating systems supported: Yes | Web-based management: Yes | WLAN data transfer rate (max): 1800 Mbit/s | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Networking standards: IEEE 802.11ac | Networking standards: IEEE 802.11a | Security algorithms: WPA-PSK | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Security algorithms: WPA2-PSK | WPS push button: Yes | Networking standards: IEEE 802.11ax | Security algorithms: WPA | Security algorithms: WMM | Security algorithms: 128-bit WEP | Networking standards: IEEE 802.11b

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950