



TP-Link Archer AX72 wireless router Gigabit Ethernet Dual-band (2.4 GHz 5 GHz) Black

Model: ARCHER AX72

Manufacturer: TP-LINK

EAN: 4897098687215

Product Code: 200206

R2,101

Firewall: Yes | Height: 49.2 mm | Access Control List (ACL): Yes | Product type: Portable router | Top Wi-Fi standard: Wi-Fi 6 (802.11ax) | DoS attack prevention: Yes | WAN connection type: RJ-45 | DSL WAN: Yes | IP address filtering: Yes | Ethernet LAN: Yes | WLAN data transfer rate (first band): 4804 Mbit/s | Depth: 147.2 mm | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Wi-Fi standards: 802.11b | Parental control: Yes | Built-in processor: Yes | Wi-Fi standards: Wi-Fi 4 (802.11n) | Wi-Fi standards: 802.11g | Wi-Fi standards: 802.11a | Wi-Fi standards: Wi-Fi 6 (802.11ax) | WLAN data transfer rate (max): 5400 Mbit/s | WPS push button: Yes | USB port: Yes | Port triggering: Yes | Universal Plug and Play (UPnP): Yes | DMZ support: Yes | On/off switch: Yes | Ethernet LAN interface type: Gigabit Ethernet | Dynamic DNS (DDNS): Yes | Width: 272.5 mm | WLAN data transfer rate (second band): 574 Mbit/s | Port forwarding: Yes | Antennas quantity: 6 | Cabling technology: 10/100/1000Base-T(X) | Operating temperature (T-T): 0 - 40 °C | Product colour:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Black | Operating relative humidity (H-H): 10 - 90% | Ethernet LAN data rates: 10 | Ethernet LAN data rates: 100 Mbit/s | MIMO: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Modulation: OFDM | Modulation: 1024-QAM | Ethernet LAN (RJ-45) ports: 4 | Ethernet LAN data rates: 1000 | DHCP client: Yes | Ethernet WAN: Yes | Filtering: Yes | Reset button: Yes | Network address translation (NAT): Yes | Processor cores: 2 | Processor frequency: 1000 MHz | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 1 | Power source type: DC | Networking standards: IEEE 802.11ax | Security algorithms: WPA | Security algorithms: WPA-Enterprise | Web-based management: Yes | MAC address filtering: Yes | Security algorithms: WPA2 | Security algorithms: WPA2-Enterprise | Networking standards: IEEE 802.11ac | Networking standards: IEEE 802.11a | Networking standards: IEEE 802.11g | Security algorithms: WPA3 | Storage relative humidity (H-H): 5 - 90% | Warnings: The product may emit radio waves that may interfere with other electronic devices. | Warnings: Do not open the appliance housing - risk of electric shock. | Networking standards: IEEE 802.11b | Warnings: Avoid contact with liquids as this may cause electric shock. | Antenna design: External | MU-MIMO technology: Yes | Support Samba (storage): Yes | Wireless Distribution System (WDS) bridge: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950