

TP-Link AX3000 Whole Home Mesh WiFi 6 System, 3-Pack

TP-Link AX3000 Whole Home Mesh WiFi 6 System, 3-Pack



Model: DECO X50(3-PACK)

Manufacturer: TP-LINK

EAN: 4897098687086

Product Code: 200208

R5,457

Security algorithms: WPA-PSK | Networking standards: IEEE 802.11b | Security algorithms: WPA3-PSK
| Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Security algorithms:
WPA2-PSK | AC adapter output voltage: 12 V | Networking standards: IEEE 802.11a | Reset button:
Yes | DHCP client: Yes | DC-in jack: Yes | Product colour: White | Networking standards: IEEE
802.11ac | Antenna type: Internal | AC adapter output current: 1.5 A | Ethernet LAN (RJ-45) ports: 3 |
Number of units included: 3 pc(s) | AC adapter included: Yes | Operating temperature (T-T): 0 - 40 °C
| Processor frequency: 1 GHz | Compliance certificates: RoHS | Compliance certificates: CE |
Warnings: Do not open the appliance housing - risk of electric shock. | Warnings: The product may
emit radio waves that may interfere with other electronic devices. | Warnings: Avoid contact with
liquids as this may cause electric shock. | Package weight: 2.18 kg | Harmonized System (HS) code:
85171800 | Firmware upgradeable via: Network | Wi-Fi standards: Wi-Fi 4 (802.11n) | Antennas
quantity: 2 | WLAN data transfer rate (second band): 2402 Mbit/s | Width: 110 mm | Wi-Fi standards:
802.11a | Wi-Fi standards: Wi-Fi 6 (802.11ax) | IGMP snooping: Yes | Ethernet cable: Yes | Wi-Fi

standards: 802.11g | Wi-Fi standards: 802.11b | Parental control: Yes | Number of products included:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

3 pc(s) | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Processor cores: 2 | Top Wi-Fi standard: Wi-Fi 6 (802.11ax) | Depth: 110 mm | Operating relative humidity (H-H): 10 - 90% | WLAN data transfer rate (first band): 574 Mbit/s | Package width: 369 mm | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | Package height: 125 mm | Firewall security: SPI | Built-in processor: Yes | Dynamic DNS (DDNS): Yes | Transmit power: CE: 20 dBm (2.4 GHz) 23 dBm (5 GHz) FCC: 30 dBm (2.4 GHz) 30 dBm (5 GHz) | Height: 114 mm | Package depth: 276.5 mm | Port forwarding: Yes | IGMP proxy: Yes | Universal Plug and Play (UPnP): Yes | Storage relative humidity (H-H): 5 - 90% | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | MU-MIMO technology: Yes | Parental control features: Custom profiles, Time controls, Weekly/monthly reports | Number of guest networks (2.4 GHz): 1 | Number of guest networks (5 GHz): 1 | BeamForming: Yes | Tagged VLAN: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950