



TP-Link Archer AX3000 Multi- Gigabit Wi-Fi 6 Router with 2.5G Port



Model: Archer AX55 Pro

Manufacturer: TP-LINK

EAN: 4897098686805

Product Code: 200211

R1,721

NAT functionality: • Port Forwarding • Port Triggering • DMZ • UPnP | VPN support: OpenVPN, PPTP, L2TP | Certification: FCC, CE, RoHS | VPN server: OpenVPN, PPTP, L2TP | Antenna design: External | Number of guest networks (5 GHz): 1 | Media server: Yes | Support Samba (storage): Yes | Number of guest networks (2.4 GHz): 1 | USB sharing: Yes | Warnings: The product may emit radio waves that may interfere with other electronic devices. | Warnings: Avoid contact with liquids as this may cause electric shock. | Indication light: Yes | Dynamic DNS (DDNS): Yes | Port triggering: Yes | WLAN data transfer rate (first band): 2402 Mbit/s | DMZ support: Yes | DSL WAN: No | WPS push button: Yes | DHCP server: Yes | Firewall security: SPI Firewall | SIM card slot: No | Guest access: Yes | 3G/4G USB modem compatibility: No | Antenna included: Yes | WLAN data transfer rate (second band): 574 Mbit/s | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | Warnings: Do not open the appliance housing - risk of electric shock. | Firewall: Yes | Port forwarding: Yes | Parental control: Yes | DoS attack prevention: Yes | WAN connection type: RJ-45 | USB port: Yes | Built-in FTP server: Yes | Universal Plug and Play

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

(UPnP): Yes | Stateful Packet Inspection (SPI): Yes | Product colour: Black | Networking standards: IEEE 802.11b | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Security algorithms: WPA2 | Networking standards: IEEE 802.11ax | Security algorithms: WPA | Networking standards: IEEE 802.11a | Security algorithms: WPA3 | Networking standards: IEEE 802.11ac | Network address translation (NAT): Yes | Quick installation guide: Yes | Width: 261.1 mm | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 1 | AC adapter included: Yes | Ethernet LAN: Yes | Operating temperature (T-T): 0 - 40 °C | Ethernet LAN (RJ-45) ports: 5 | DHCP client: Yes | Ethernet WAN: Yes | Antenna type: 2x2 | Reset button: Yes | Number of products included: 1 pc(s) | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Cables included: LAN (RJ-45) | Product type: Desktop/pole router | WLAN data transfer rate (max): 2402 Mbit/s | Depth: 134.5 mm | Operating relative humidity (H-H): 10 - 90% | Top Wi-Fi standard: Wi-Fi 6 (802.11ax) | Antennas quantity: 4 | Wi-Fi standards: Wi-Fi 6 (802.11ax) | Height: 41 mm | Storage relative humidity (H-H): 5 - 90% | On/off switch: Yes | Power source type: DC | Ethernet LAN interface type: Gigabit Ethernet

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950