



TP-Link Archer AX5400 Multi- Gigabit WiFi 6 Router



Model: Archer AX72 PRO

Manufacturer: TP-LINK

EAN: 4897098686775

Product Code: 200212

R2,769

VPN support: OpenVPN, PPTP | Certification: FCC, CE, RoHS | NAT functionality: Port Forwarding Port Triggering DMZ UPnP Virtual Server | Security algorithms: WPA3 | Storage relative humidity (H-H): 5 - 90% | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Networking standards: IEEE 802.11ac | Wi-Fi standards: Wi-Fi 6 (802.11ax) | WPS push button: Yes | WLAN data transfer rate (max): 4804 Mbit/s | High power: Yes | Networking standards: IEEE 802.11a | WLAN data transfer rate (second band): 574 Mbit/s | Firewall: Yes | Number of products included: 1 pc(s) | Ethernet LAN (RJ-45) ports: 5 | Parental control: Yes | WAN connection type: RJ-45 | Reset button: Yes | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | Product colour: Black | Quick installation guide: Yes | AC adapter included: Yes | Port forwarding: Yes | DMZ support: Yes | Product type: Desktop/pole router | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Firewall security: SPI Firewall | Built-in processor: Yes | Universal Plug and Play (UPnP): Yes | WLAN data transfer rate (first band): 4804 Mbit/s | Operating temperature (T-T): 0 - 40 °C | DHCP server: Yes | Cables included: LAN (RJ-45) | Ethernet LAN: Yes | SIM card slot: No | Port triggering: Yes | Antenna type: 3x3 |

Operating relative humidity (H-H): 10 - 90% | Depth: 147.2 mm | Width: 272.5 mm | Ethernet LAN

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

interface type: Gigabit Ethernet | Dynamic DNS (DDNS): Yes | Height: 49.2 mm | Antenna included: Yes | Guest access: Yes | On/off switch: Yes | Indication light: Yes | Static route: Yes | Network address translation (NAT): Yes | Processor frequency: 1000 MHz | Antennas quantity: 6 | DHCP client: Yes | DSL WAN: No | Stateful Packet Inspection (SPI): Yes | USB port: Yes | DoS attack prevention: Yes | Built-in FTP server: Yes | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 1 | Ethernet WAN: Yes | 3G/4G USB modem compatibility: No | Power source type: DC | Processor cores: 2 | Networking standards: IEEE 802.11b | Networking standards: IEEE 802.11ax | Security algorithms: WPA | Security algorithms: WPA2 | Top Wi-Fi standard: Wi-Fi 6 (802.11ax) | Number of guest networks (5 GHz): 1 | Support Samba (storage): Yes | VPN server: OpenVPN, PPTP | USB sharing: Yes | Antenna design: External | Media server: Yes | Number of guest networks (2.4 GHz): 1 | Warnings: The product may emit radio waves that may interfere with other electronic devices. | Warnings: Do not open the appliance housing - risk of electric shock. | Warnings: Avoid contact with liquids as this may cause electric shock.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950