



TP-Link Omada AX3000 Gigabit VPN Router



Model: ER706W

Manufacturer: TP-LINK

EAN: 4895252500691

Product Code: 200216

R3,342

Certification: CE, FCC, RoHS | Ethernet LAN: Yes | Ethernet LAN data rates: 100 Mbit/s | Operating relative humidity (H-H): 10 - 90% | Network address translation (NAT): Yes | Ethernet LAN data rates: 1000 | DSL WAN: No | Height: 35 mm | Access Control List (ACL): Yes | Universal Plug and Play (UPnP): Yes | Output current: 2 A | Reset button: Yes | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | Internal memory: 512 MB | Operating temperature (T-T): 0 - 40 °C | Antenna gain level (max): 4.5 dBi | Filtering: Yes | Ethernet LAN interface type: Gigabit Ethernet | Antennas quantity: 3 | Cabling technology: 10/100/1000Base-T(X) | Product type: Desktop/pole router | Wall mountable: Yes | MIMO: Yes | Storage temperature (T-T): -40 - 70 °C | Ethernet LAN data rates: 10 | LED indicators: System, USB, WAN, WLAN | AC adapter included: Yes | DHCP server: Yes | Output voltage: 12 V | Depth: 131 mm | VPN tunnels quantity: 50 | Ethernet LAN (RJ-45) ports: 4 | Product colour: Black | Manual: Yes | Flash memory: 128 MB | DC-in jack: Yes | Internal memory type: DDR4 | USB port: Yes | Power source type: DC | Ethernet WAN: Yes | Security algorithms: WPA | Security algorithms: WPA2 | Security algorithms: WPA3-Enterprise | Web-based management: Yes | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 1 | Storage relative humidity (H-H): 5 - 90% | WLAN data transfer rate (max): 3000 Mbit/s | Width: 226 mm | Routing protocols: RIP | Routing protocols: OSPF | System event log: Yes |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

URL filtering: Yes | WAN connection type: SFP | 3G/4G USB modem compatibility: Yes | Antenna design: External | WLAN data transfer rate (first band): 574 Mbit/s | MU-MIMO technology: Yes | WLAN data transfer rate (second band): 2402 Mbit/s | Port triggering: Yes | DMZ support: Yes | SIM card slot: No | Guest access: Yes | Dynamic DNS (DDNS): Yes | Port forwarding: Yes | Schedule access: Yes | Warnings: The product may emit radio waves that may interfere with other electronic devices. | Warnings: Do not open the appliance housing - risk of electric shock. | Warnings: Avoid contact with liquids as this may cause electric shock.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950