



TP-Link 16-Port Gigabit Desktop Switch with 16-Port PoE+



Model: TL-SG116P

Manufacturer: TP-LINK

EAN: 4895252500301

Product Code: 200251

R3,073

AC input frequency: 50 Hz | Operating temperature (T-T): 0 - 40 °C | Package height: 70 mm | VLAN support: Yes | Networking standards: IEEE 802.3u | Rate limiting: Yes | Cable types supported: Cat3 | Cable types supported: Cat4 | Operating relative humidity (H-H): 10 - 90% | Storage temperature (T-T): -40 - 70 °C | Width: 286 mm | Copper ethernet cabling technology: 100BASE-TX | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Storage relative humidity (H-H): 5 - 90% | Power consumption (max): 144.28 W | Power supply included: Yes | DC input voltage: 9 V | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Wall mountable: Yes | Forwarding rate: 23.81 Mpps | Networking standards: IEEE 802.1Q | Cable types supported: Cat6 | Basic switching RJ-45 Ethernet ports quantity: 16 | IGMP snooping: Yes | Quick start guide: Yes | Switching capacity: 32 Gbit/s | Gigabit Ethernet (copper) ports quantity: 16 | Store-and-forward: Yes | Cable types supported: Cat5 | Cable types supported: Cat5e | Package width: 227 mm | Jumbo frames support: Yes | Copper ethernet cabling technology: 10BASE-T | Housing material: Metal | Product colour: Black | Auto MDI/MDI-X: Yes | Height: 25.4 mm | Full duplex: Yes | Jumbo frames: 9000 | Power over Ethernet (PoE): Yes | Package weight: 2 kg |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Packet buffer memory: 4.1 MB | Port mirroring: Yes | MAC address table: 8000 entries | Auto-negotiation: Yes | LED indicators: Yes | Quality of Service (QoS) support: Yes | Flow control support: Yes | Cable length detection: Yes | Power consumption (typical): 11.72 W | Switch type: Unmanaged | Heat dissipation: 490.55 BTU/h | Number of VLANs: 32 | AC input voltage: 220 V | Number of queues: 4 | Input current: 0.6 A | Loop protection: Yes | Virtual LAN features: Protocol-based VLAN | Copper ethernet cabling technology: 1000BASE-T | Virtual LAN features: Tagged VLAN | Depth: 111.7 mm | Stackable: Yes | Package depth: 434 mm | Link aggregation: Yes | Broadcast storm control: Yes | Warnings: Do not open the case or try to repair it yourself. | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950