



TP-Link LiteWave 5-Port Gigabit Desktop Switch with 4- Port PoE+



Model: LS105GP

Manufacturer: TP-LINK

EAN: 4895252504545

Product Code: 200252

R1,169

Certification: CE, FCC, RoHS | Basic switching RJ-45 Ethernet ports quantity: 5 | 10G support: No |
Warnings: Ensure the unit is adequately ventilated during operation. | DC input voltage: 53.5 V |
Networking standards: IEEE 802.3at | AC input frequency: 50 Hz | Flow control support: Yes |
Warnings: Do not open the case or try to repair it yourself. | Networking standards: IEEE 802.3af |
Switch type: Unmanaged | User guide: Yes | Jumbo frames: 16000 | Heat dissipation: 253.16 BTU/h |
MAC address table: 2000 entries | Forwarding rate: 7.44 Mpps | Networking standards: IEEE 802.3ab
| Networking standards: IEEE 802.1p | Store-and-forward: Yes | Storage relative humidity (H-H): 5 -
90% | Total Power over Ethernet (PoE) budget: 65 W | Networking standards: IEEE 802.3i | Operating
relative humidity (H-H): 10 - 90% | Switching capacity: 10 Gbit/s | Networking standards: IEEE 802.3x
| Power consumption (max): 74.46 W | Operating temperature (T-T): 0 - 40 °C | Storage temperature
(T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | IGMP snooping: Yes | LED indicators: Yes |
MAC address auto-aging supported: Yes | Power over Ethernet (PoE) ports quantity: 4 | Power over

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Product colour: Black | Power over Ethernet (PoE): Yes | MAC address auto-learning supported: Yes | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Cable types supported: Cat4 | Power supply included: Yes | Cable types supported: Cat3 | Power source: DC/PoE | Cable types supported: Cat5 | Cable types supported: Cat5e | Auto-negotiation: Yes | Networking standards: IEEE 802.3u | Package type: Box | Height: 25 mm | Width: 99.8 mm | AC input voltage: 220 V | Auto MDI/MDI-X: Yes | Depth: 98 mm

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950