



TP-Link LiteWave 10- Port Gigabit Desktop Switch with 8-Port PoE+



Model: LS1210GP

Manufacturer: TP-LINK

EAN: 4895252504569

Product Code: 200254

R1,688

Certification: CE, FCC, RoHS | Power supply included: Yes | Width: 209 mm | SFP module slots quantity: 1 | AC input frequency: 50 Hz | Heat dissipation: 261.66 BTU/h | LED indicators: Yes | Warnings: Ensure the unit is adequately ventilated during operation. | Switching capacity: 20 Gbit/s | Switch type: Unmanaged | AC input voltage: 220 V | Power consumption (max): 76.96 W | Basic switching RJ-45 Ethernet ports quantity: 9 | Operating relative humidity (H-H): 10 - 90% | Warnings: Do not open the case or try to repair it yourself. | Power over Ethernet (PoE) ports quantity: 8 | Package type: Box | Power over Ethernet (PoE): Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | 10G support: No | Operating temperature (T-T): 0 - 40 °C | Total Power over Ethernet (PoE) budget: 61 W | User guide: Yes | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Product colour: Black | Networking standards: IEEE 802.3x |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Power source: DC/PoE | Height: 26 mm | Networking standards: IEEE 802.3at | Depth: 126 mm | Storage relative humidity (H-H): 5 - 90% | MAC address table: 4000 entries | Networking standards: IEEE 802.3i | Networking standards: IEEE 802.3af | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Networking standards: IEEE 802.3z | Networking standards: IEEE 802.3u | Auto MDI/MDI-X: Yes | Auto-negotiation: Yes | Jumbo frames: 16000 | DC input voltage: 53.5 V | Forwarding rate: 14.88 Mpps | Cable types supported: Cat5 | Cable types supported: Cat5e | Cable types supported: Cat4 | Cable types supported: Cat3 | Store-and-forward: Yes | Flow control support: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950