



TP-Link Omada ES220GMP network switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black

Model: ES220GMP

Manufacturer: TP-LINK

EAN: 8885020625943

Product Code: 200257

R4,435

Unified static configuration: Yes | Zero Touch Provisioning (ZTP): Yes | Firmware upgradeable: Yes |
LED indicators: Yes | AC input frequency: 50/60 Hz | Networking standards: IEEE 802.3z | Networking
standards: IEEE 802.3u | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x |
AC input voltage: 100 - 240 V | Networking standards: IEEE 802.1ab | Web-based management: Yes |
Product colour: Black | Networking standards: IEEE 802.3i | Package type: Box | Networking
standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Height: 44 mm | Cables included: AC |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Power over Ethernet (PoE) power per port: 30 W | Storage relative humidity (H-H): 5 - 90% | Noise level: 41.5 dB | Power over Ethernet (PoE): Yes | Power consumption (max): 289.7 W | Switching capacity: 40 Gbit/s | Surge protection: Yes | Operating temperature (T-T): -5 - 50 °C | Total Power over Ethernet (PoE) budget: 250 W | Number of fans: 2 fan(s) | Width: 440 mm | Jumbo frames support: Yes | Auto MDI/MDI-X: Yes | Depth: 180 mm | Mean time between failures (MTBF): 310550.7 h | Power source: AC | User guide: Yes | Rack mounting: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | SFP module slots quantity: 2 | Operating relative humidity (H-H): 10 - 90% | VLAN support: Yes | Power supply included: Yes | Flash memory: 64 MB | Link aggregation: Yes | Gigabit Ethernet (copper) ports quantity: 18 | Jumbo frames: 15000 | Packet buffer memory: 4 MB | Cloud-managed: Yes | MAC address table: 8000 entries | Auto-negotiation: Yes | Loop protection: Yes | Heat dissipation: 984.88 BTU/h | Store-and-forward: Yes | DHCP features: DHCP client | Forwarding rate: 29.76 Mpps | Switch type: Managed | IGMP snooping: Yes | Compliance certificates: Federal Communications Commission (FCC) | Virtual LAN features: MTU VLAN | Port mirroring: Yes | 10G support: No | Flow control support: Yes | Queue scheduling algorithms: Weighted Round Robin (WRR) | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Compliance certificates: RoHS | Compliance certificates: CE | Virtual LAN features: Port-based VLAN | Number of VLANs: 32 | Power connector: AC-in jack | Power over Ethernet plus (PoE+) ports quantity: 16 | Surge protection voltage: 6 kV | Stackable: No | Virtual LAN features: Tagged VLAN | Fast leave: Yes | Power over Ethernet (PoE) type supported: PoE+ | Switch layer: L2 | Rack mount kit: Yes | Basic switching RJ-45 Ethernet ports quantity: 18

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950