



Synology RackStation RS822RP+ NAS/storage server Rack (1U) Ryzen Embedded V1500B 2 GB DDR4 0 TB DiskStation Manager Grey

Model: RS822RP+

Manufacturer: SYNOLOGY

EAN: 4711174724758

Product Code: 20052

R35,545

Certification: FCC CE BSMI VCCI RCM UKCA EAC CCC KC UL | Online RAID migration: Yes | RAID levels: 10 | ECC: Yes | On/off switch: Yes | Supported file systems: ext4 | Operating relative humidity (H-H): 8 - 80% | Processor family: Ryzen Embedded | RAID levels: 6 | RAID levels: 0 | Supported file

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

systems: HFS+ | Total installed storage capacity: 0 TB | Internal memory type: DDR4 | USB port: Yes | Product colour: Grey | Online RAID expansion: Yes | Number of fans: 2 fan(s) | Ethernet LAN data rates: 1000 Mbit/s | Mac operating systems supported: Yes | Chassis type: Rack (1U) | Security algorithms: HTTPS | Wake-on-LAN ready: Yes | Supported storage drive types: HDD & SSD | Third-party support: Yes | Browser supported: Google Chrome, Firefox, Microsoft Edge, Safari | Storage relative humidity (H-H): 5 - 95% | Type: NAS | Security algorithms: SSL/TLS | Supported storage drive interfaces: Serial ATA II, Serial ATA III | Backup features: Cloud | Cooling type: Active | Drive bay locking: Yes | Installed storage drive type: No | Built-in FTP server: Yes | Weight: 8 kg | Processor threads: 8 | Multilingual support: Yes | RAID support: Yes | Memory form factor: SO-DIMM | Maximum RAM supported: 32 GB | Reset button: Yes | Hot spare: Yes | eSATA ports quantity: 1 | Snapshot: Yes | WLAN adapter supported: Yes | Windows operating systems supported: Yes | Processor cores: 4 | Storage drives installed: No | Concurrent connections: 500 | PCI Express x8 (Gen 3.x) slots: 1 | Processor model: V1500B | Processor generation: AMD Ryzen Embedded V1000 Series | On-board graphics card model: Not available | Cables included: AC | L3 cache: 4 MB | Memory slots: 2 | Link aggregation: Yes | Operating system installed: DiskStation Manager | Fan diameter: 4 cm | Ethernet LAN (RJ-45) ports: 4 | Supported file systems: BTRFS | RAID levels: JBOD | Supported file systems: FAT32 | Power consumption (HDD standby): 16.7 W | RAID levels: 1 | Number of storage drives supported: 4 | Supported file systems: ext3 | Supported file systems: NTFS | AC input frequency: 50/60 Hz | RAID levels: 5 | Supported file systems: exFAT | Width: 480 mm | Backup function: Yes | Redundant power supply (RPS) support: Yes | Hot-swap drive bays: Yes | iSCSI support: Yes | Operating temperature (T-T): 0 - 35 °C | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 2 | Height: 44 mm | System log: Yes | Backup features: iSCSI LUN | Storage temperature (T-T): -20 - 60 °C | Security algorithms: SSH | Storage drive sizes supported: 2.5 | Number of users: 2048 user(s) | L2 cache: 2 MB | Power supply location: Built-in | Storage drive sizes supported: 3.5" | Depth: 518.6 mm | Internal memory: 2 GB | Supported network protocols: SMB1 (CIFS), SMB2, SMB3, NFSv3, NFSv4, NFSv4.1, NFS Kerberized sessions, iSCSI, HTTP, HTTPS, FTP, SNMP, LDAP, CalDAV | Ethernet LAN: Yes | Noise level: 38.8 dB | Power cables quantity: 2 | Built-in iTunes server: Yes | Number of processors supported: 1 | Linux operating systems supported: Yes | Power supply unit (PSU) capacity: 150 W | LED indicators: HDD | Device class: Small & Medium Business | LED indicators: Status | Power consumption (typical): 47.69 W | Processor frequency: 2.2 GHz | LED indicators: Power | Operating altitude: 0 - 5000 m | Share folder: SMB/AFP/NFS/FTP/WebDAV | LED indicators: Alarm | AC input voltage: 100 - 240 V | Processor manufacturer: AMD | Access Control List (ACL): Yes | Compliance certificates: RoHS

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950