



Synology RackStation RS3621RPXS NAS/storage server Rack (2U) Ethernet LAN Black D-1531

Model: RS3621RPxs

Manufacturer: SYNOLOGY

EAN: 4711174724062

Product Code: 20063

R97,908

Certification: FCC CE BSMI VCCI RCM EAC CCC KC UL | Fan diameter: 8 cm | Cooling type: Active | Idle States: Yes | Internal memory type: DDR4 | USB port: Yes | Built-in display: No | Storage drive interface: Serial ATA II, Serial ATA III | Intel Secure Key Technology version: 1.00 | Height: 88 mm | Storage temperature (T-T): -20 - 60 °C | PCI Express x8 (Gen 3.x) slots: 2 | Installed storage drive type: No | Memory form factor: UDIMM | Maximum RAM supported: 64 GB | Storage drive sizes supported: 3.5" | Power supply unit (PSU) capacity: 500 W | Intel VT-x with Extended Page Tables (EPT): Yes | Noise level: 50.2 dB | Backup function: Yes | Intel Enhanced Halt State: Yes | Operating temperature (T-T): 0 - 35 °C | Depth: 724 mm | Ethernet LAN: Yes | Number of fans: 4 fan(s) | Memory slots: 4 | Processor frequency: 2.2 GHz | Intel 64: Yes | Intel Virtualization Technology for

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Directed I/O (VT-d): Yes | Intel Virtualization Technology (VT-x): Yes | Internal memory: 8 GB |
Enhanced Intel SpeedStep Technology: Yes | Storage drives installed: No | Width: 482 mm |
Redundant power supply (RPS) support: Yes | Processor manufacturer: Intel | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 2 | Type: Storage server | Intel Trusted Execution Technology: Yes |
Number of storage drives supported: 12 | Built-in speaker(s): No | Conflict-Free processor: Yes |
Processor family: Intel® Xeon® | Harmonized System (HS) code: 84714100 | Intel TSX-NI: Yes |
Power consumption (HDD standby): 65.94 W | Power consumption (typical): 140.01 W | Intel TSX-NI version: 1.00 | Execute Disable Bit: Yes | Processor cores: 6 | Chassis type: Rack (2U) | Processor model: D-1531 | Operating relative humidity (H-H): 5 - 95% | Storage drive sizes supported: 2.5" |
Device class: Small & Medium Business | ECC: Yes | On/off switch: Yes | Power cables quantity: 2 |
Processor boost frequency: 2.7 GHz | Embedded options available: No | On-board graphics card model: Not available | Wake-on-LAN ready: Yes | Supported storage drive types: HDD & SSD | RAID support: Yes | Weight: 14.5 kg | AC input voltage: 100 - 240 V | AC input frequency: 50 - 60 Hz |
Ethernet LAN (RJ-45) ports: 4 | CPU configuration (max): 1 | Product colour: Black

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950