



Synology RackStation RS1619XS+ NAS/storage server Rack (1U) Intel Xeon D D- 1527 8 GB DDR4 0 TB DiskStation Manager Black

Model: RS1619xs+

Manufacturer: SYNOLOGY

EAN: 4711174723065

Product Code: 20064

R70,413

Certification: EAC VCCI RCM FCC CE BSMI | Compliance certificates: RoHS | Warnings: Do not dismantle the appliance yourself. | Warnings: Do not dispose of the device in the regular rubbish bin. The product requires special disposal. | Warnings: Avoid contact with liquids. | Browser supported: Chrome, Firefox, Internet Explorer 10+, Safari 10+ | Operating system installed: DiskStation Manager | Memory channels supported by processor: Dual | Storage drive sizes supported: 2.5" | Height: 44 mm | Storage drive sizes supported: 3.5" | Memory slots: 4 | Intel® Secure Key: Yes |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Number of storage drives supported: 4 | Intel TSX-NI: Yes | Chassis type: Rack (1U) | Execute Disable Bit: Yes | Maximum internal memory supported by processor: 128 GB | Thermal Design Power (TDP): 35 W | Processor socket: BGA 1667 | LED indicators: Status | Installed storage drive type: No | Storage drive interface: Serial ATA, Serial ATA II, Serial ATA III | Processor code: SR2DK | Supported network protocols: CIFS, AFP, NFS, FTP, WebDAV, CalDAV, iSCSI, Telnet, SSH, SNMP, VPN (PPTP, OpenVPN, L2TP) | Memory types supported by processor: DDR4-SDRAM | Processor ARK ID: 91195 | Ethernet LAN: Yes | Intel® OS Guard: Yes | PCI Express configurations: 1x8 | CPU configuration (max): 1 | USB port: Yes | Width: 480 mm | Backup function: Yes | AC input frequency: 50 - 60 Hz | On/off switch: Yes | Memory types supported by processor: DDR3-SDRAM | Intel VT-x with Extended Page Tables (EPT): Yes | Number of fans: 2 fan(s) | PCI Express slots version: 2.0 | AC input voltage: 100 - 240 V | Intel TSX-NI version: 1.00 | Processor manufacturer: Intel | Idle States: Yes | Wi-Fi: No | Ethernet LAN data rates: 100 | Power consumption (typical): 68.68 W | Intel 64: Yes | Processor boost frequency: 2.7 GHz | Fan diameter: 4 cm | Intel Virtualization Technology (VT-x): Yes | LED indicators: Power | Processor lithography: 14 nm | LED indicators: HDD | Ethernet LAN data rates: 1000 Mbit/s | Conflict-Free processor: Yes | Depth: 518.6 mm | Thermal Monitoring Technologies: Yes | PCI Express configurations: 1x4 | PCI Express slots version: 3.0 | Wake-on-LAN ready: Yes | Supported storage drive types: HDD & SSD | Server operating systems supported: Windows Server 2016 | Scalability: 1S | Product colour: Black | Reset button: Yes | LED indicators: Alarm | Ethernet LAN data rates: 10 | PCI Express configurations: 1x16 | Processor package size: 37.5 x 37.5 mm | Web-based management: Yes | Backup features: Cloud | iSCSI support: Yes | Supported file systems: BTRFS | Supported file systems: HFS+ | Number of M.2 (M & B) slots: 2 | Supported file systems: ext4 | Power consumption (HDD standby): 34.78 W | Expansion ports quantity: 1 | Access Control List (ACL): Yes | Link aggregation: Yes | Device class: Small & Medium Business | Multilingual support: Yes | Total installed storage capacity: 0 TB | Supported file systems: Fat | Supported file systems: ext3 | Supported file systems: NTFS | Power supply location: Built-in | Maximum RAM supported: 64 GB | Backup features: iSCSI LUN | Storage drive capacity: 0 GB | Number of power supply units: 2 | Ethernet LAN (RJ-45) ports: 4 | Internal memory type: DDR4 | Storage temperature (T-T): -20 - 60 °C | Enhanced Intel SpeedStep Technology: Yes | Weight: 8.16 kg | Processor cache type: L3 | Noise level: 39.3 dB | On-board graphics card model: Not available | Internal memory: 8 GB | Embedded options available: Yes | Mac operating systems supported: Mac OS X 10.14 Mojave | Processor frequency: 2.2 GHz | Windows operating systems supported: Windows 7 | Stepping: V2 | Mac operating systems supported: Mac OS X 10.11 El Capitan | Operating altitude: 0 - 5000 m | Mac operating systems supported: Mac OS X 10.12 Sierra | Storage drives installed: No | Processor cores: 4 | Processor model: D-1527 | Windows operating systems supported: Windows 10 | Cables included: AC | Mac

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

operating systems supported: Mac OS X 10.13 High Sierra | ECC supported by processor: Yes | Processor threads: 8 | RAID levels: 1 | Intel® Hyper Threading Technology (Intel® HT Technology): Yes | RAID levels: JBOD | Intel Enhanced Halt State: Yes | Processor series: Intel Xeon D-1500 | Security algorithms: HTTPS | Intel Virtualization Technology for Directed I/O (VT-d): Yes | Harmonized System (HS) code: 84714100 | Security algorithms: SSL/TLS | Operating temperature (T-T): 5 - 35 °C | RAID levels: 10 | Operating relative humidity (H-H): 5 - 95% | RAID levels: 5 | Intel Trusted Execution Technology: Yes | Processor family: Intel® Xeon® D | Security algorithms: SSH | RAID levels: 0 | Processor codename: Broadwell | Type: NAS | Maximum number of PCI Express lanes: 32 | Intel® AES New Instructions (Intel® AES-NI): Yes | UART: Yes | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 2 | Intel® Turbo Boost Technology: 2.0 | Power supply unit (PSU) capacity: 150 W | Processor operating modes: 64-bit | Quick installation guide: Yes | Intel Secure Key Technology version: 1.00 | Hot-swap drive bays: Yes | Cooling type: Active | RAID support: Yes | PCI Express x8 (Gen 3.x) slots: 1 | RAID levels: 6 | Processor cache: 6 MB

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950