



HPE MSR954 1GbE SFP Router HPE MSR954 1GbE SFP Router EU en



Model: JH296A#ABB

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 889296338239

Product Code: 202840

R17,743

The HPE MSR954 router delivers high-performance, small-branch routing in a single form factor. Featuring integrated routing, switching, wireless, security, and SIP, this router can boost your service delivery while simplifying the management of your corporate WAN. The MSR954 router provides for flexible deployment models with zero-touch provisioning and LTE connectivity. It also brings you enhanced performance to provide investment protection.

Product Description: HPE MSR954 - router - rack-mountable | Device Type: Router - 4-port switch (integrated) | Enclosure Type: Rack-mountable - 1U | WAN Ports Qty: 1 | Data Link Protocol: Ethernet, Fast Ethernet, Gigabit Ethernet | Data Transfer Rate: 1 Gbps | Performance: Forwarding performance: up to 300 Kpps Encryption throughput: up to 160 Mbps Throughput (64-byte packet size): up to 300 Kpps | Capacity: VPN tunnels: 100 IPv4 routing table entries: 10000 IPv6 routing table entries: 5000 IPv4 forwarding table entries: 10000 IPv6 forwarding table entries: 5000 |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Network / Transport Protocol: TCP/IP, UDP/IP, NTP, IPSec, ARP | Routing Protocol: OSPF, EGP, BGP-4, IS-IS, RIP-1, RIP-2, IGMPv2, IGMP, IGMPv3, OSPFv3, Bidirectional PIM, MSDP, static IPv4 routing, static IPv6 routing, ECMP, BGP-4+, BGP+ | Remote Management Protocol: SNMP 1, SNMP 2, RMON, Telnet, SNMP 3, TFTP, CLI | Features: NAT support, VLAN support, port mirroring, WRED, sFlow, STP support, RSTP support, MSTP support, tunnelling, ACL support, QoS, CAR, URPF, DHCP relay, MIB, port isolation, packet storm protection, CoS, Loopback, DVPN, MBGP, RED | Compliant Standards: IEEE 802.2, IEEE 802.3, IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1s | Power: AC 120/230 V | Dimensions (WxDxH): 26.6 cm x 16.1 cm x 4.36 cm | Weight: 1 kg | Localisation: English / Europe | Manufacturer Warranty: 1-year warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950