TP-LINK AX1500 Dual-Band Wi-Fi 6 Router 300 Mbps at 2.4 GHz + 1201 Mbps at 5 GHz

Model: MR60X

Manufacturer: TP-LINK

EAN: 6957939001223

Product Code: 202926

R1,158

The Mercusys MR60X V2 is designed to enhance your networking experience with a performance of 1.5 Gbps. Supporting dual-band connectivity across both 2.4 GHz and 5 GHz frequencies, it ensures stable and efficient connections for various devices. Equipped with features like MU-MIMO technology and beamforming, this wireless router offers improved coverage, allowing multiple users to connect seamlessly without compromising speed.

With security measures such as WPA3 encryption and a Stateful Packet Inspection Firewall, the MR60X V2 prioritizes your online safety while providing easy network management through its parental controls and guest network features. Designed for versatility, it comes with both wired and wireless options, making it suitable for a range of environments from home to office setups.

Product Description: Mercusys MR60X V2 - wireless router - Wi-Fi 6 - desktop | Device Type: Wireless router - 2-port switch (integrated) | Enclosure Type: Desktop | WAN Ports Qty: 1 | Data Link Protocol:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Ethernet, Fast Ethernet, Gigabit Ethernet, IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, IEEE 802.11n, IEEE 802.11ac, 802.11ax | Frequency Band: 2.4 GHz / 5 GHz | Data Transfer Rate: 1.5 Gbps | Performance: Maximum data rate (2.4 GHz): 300 Mbps Maximum data rate (5 GHz): 1201 Mbps | Network / Transport Protocol: PPTP, L2TP, PPPoE, DHCP, IPv4, IPv6 | Routing Protocol: IGMP, static IP routing | Remote Management Protocol: DHCP | Features: IGMP snooping, parental control, WMM support, QoS, WPS, DHCP server, port forwarding, reset button, port triggering, SPIF, IP-MAC binding, DHCP client, IGMP proxy, MU-MIMO technology, beamforming technology, Smart Connect, DMZ support, VLAN Tagging, IPTV support, BSS Coloring, Guest Network, TWT, wireless radio enable/disable | Compliant Standards: IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, IEEE 802.11n, UPnP, IEEE 802.11ac, IEEE 802.11ax, Wi-Fi CERTIFIED 6 | Dimensions (WxDxH): 17.56 cm x 15.72 cm x 4.5 cm

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950